

The SageTeX package*

Dan Drake and others†

December 19, 2016

1 Introduction

Why should the Haskell and R folks have all the fun? Literate Haskell is a popular way to mix Haskell source code and L^AT_EX documents. (Actually any kind of text or document, but here we’re concerned only with L^AT_EX.) You can even embed Haskell code in your document that writes part of your document for you. Similarly, the R statistical computing environment includes Sweave, which lets you do the same thing with R code and L^AT_EX.

The SageTeX package allows you to do (roughly) the same thing with the Sage mathematics software suite (see <http://sagemath.org>) and L^AT_EX. (If you know how to write literate Haskell: the `\eval` command corresponds to `\sage`, and the `code` environment to the `sageblock` environment.) As a simple example, imagine in your document you are writing about how to count license plates with three letters and three digits. With this package, you can write something like this:

```
There are $26$ choices for each letter, and $10$ choices for
each digit, for a total of $26^3 \cdot 10^3 =
\sage{26^3*10^3}$ license plates.
```

and it will produce

```
There are 26 choices for each letter, and 10 choices for each digit, for
a total of  $26^3 \cdot 10^3 = ??$  license plates.
```

The great thing is, you don’t have to do the multiplication. Sage does it for you. This process mirrors one of the great aspects of L^AT_EX: when writing a L^AT_EX document, you can concentrate on the logical structure of the document and trust L^AT_EX and its army of packages to deal with the presentation and typesetting. Similarly, with SageTeX, you can concentrate on the mathematical structure (“I need the product of 26^3 and 10^3 ”) and let Sage deal with the base-10 presentation of the number.

A less trivial, and perhaps more useful example is plotting. You can include a plot of the sine curve without manually producing a plot, saving an EPS or PDF

*This document corresponds to SageTeX v3.0-92d9f7a, dated 2015/08/26.

†Author’s website: mathsci.kaist.ac.kr/~drake/.


file, and doing the `\includegraphics` business with the correct filename yourself. If you write this:

Here is a lovely graph of the sine curve:

```
\sageplot[width=.75\textwidth]{plot(sin(x), x, 0, 2*pi)}
```

in your \LaTeX file, it produces

Here is a lovely graph of the sine curve:



Again, you need only worry about the logical/mathematical structure of your document (“I need a plot of the sine curve over the interval $[0, 2\pi]$ here”), while \SageTeX takes care of the gritty details of producing the file and sourcing it into your document.

But `\sageplot` isn’t magic I just tried to convince you that \SageTeX makes putting nice graphics into your document very easy; let me turn around and warn you that using graphics *well* is not easy, and no \LaTeX package or Python script will ever make it easy. What \SageTeX does is make it easy to *use Sage* to create graphics; it doesn’t magically make your graphics good, appropriate, or useful. (For instance, look at the sine plot above—I would say that a truly lovely plot of the sine curve would not mark integer points on the x -axis, but rather $\pi/2$, π , $3\pi/2$, and 2π . Incidentally, you can do this in Sage: do `sage.plot.plot?` and look for `ticks` and `tick_formatter`.)

Till Tantau has some good commentary on the use of graphics in the “Guidelines on Graphics” section of the PGF manual (chapter 7 of the manual for version 2.10). You should always give careful thought and attention to creating graphics for your document; I have in mind that a good workflow for using \SageTeX for plotting is something like this:

1. Figure out what sort of graphic you need to communicate your ideas or information.
2. Fiddle around in Sage until you get a graphics object and set of options that produce the graphic you need.
3. Copy those commands and options into \SageTeX commands in your \LaTeX document.

The \SageTeX package’s plotting capabilities don’t help you find those Sage commands to make your lovely plot, but they do eliminate the need to muck around with saving the result to a file, remembering the filename, including it into your document, and so on. In section 3, we will see what we can do with \SageTeX .

2 Installation

SageTeX needs two parts to work: a Python module known to Sage, and a L^AT_EX package known to T_EX. These two parts need to come from the same version of SageTeX to guarantee that everything works properly. As of Sage version 4.3.1, SageTeX comes included with Sage, so you only need to make `sagetex.sty`, the L^AT_EX package, known to T_EX. Full details of this are in the Sage Installation guide at sagemath.org/doc/installation/ in the obviously-named section “Make SageTeX known to T_EX”. Here’s a brief summary of how to do that:

- Copy `sagetex.sty` to the same directory as your document. This always works, but requires lots of copies of `sagetex.sty` and is prone to version skew.
- Copy the directory containing `sagetex.sty` to your home directory with a command like

```
cp -R $SAGE_ROOT/local/share/texmf ~/
```

where `$SAGE_ROOT` is replaced with the location of your Sage installation.

- Use the environment variable `TEXINPUTS` to tell T_EX to search the directory containing `sagetex.sty`; in the bash shell, you can do

```
export TEXINPUTS=$SAGE_ROOT/local/share/texmf//:
```

You should again replace `$SAGE_ROOT` with the location of your Sage installation.

The best method is likely the second; while that does require you to recopy the files every time you update your copy of Sage, it does not depend on your shell, so if you use, say, Emacs with AucT_EX or some other editor environment, everything will still work since T_EX’s internal path-searching mechanisms can find `sagetex.sty`.

Note that along with `sagetex.sty`, this documentation, an example file, and other useful scripts are all located in the directory `$SAGE_ROOT/local/share/texmf`.

2.1 SageTeX and T_EXLive

SageTeX was included in T_EXLive, which seemed nice, except that the Python module and L^AT_EX package for SageTeX need to be synchronized and the Python module in Sage was much easier to update than the L^AT_EX style file in T_EXLive. If you are so unlucky as to be using a version of T_EXLive that includes SageTeX, I strongly recommend using SageTeX only from what is included with Sage and ignoring what’s included with T_EXLive.

2.2 The `noversioncheck` option

As of version 2.2.4, `SageTeX` automatically checks to see if the versions of the style file and Python module match. This is intended to prevent strange version mismatch problems, but if you would like to use mismatched sources, you can—at your peril—give the `noversioncheck` option when you load the `SageTeX` package. Don’t be surprised if things don’t work when you do this.

If you are considering using this option because the Sage script complained and exited, you really should just get the `LATEX` and Python modules synchronized. Every copy of Sage since version 4.3.2 comes with a copy of `sagetex.sty` that is matched up to Sage’s baked-in `SageTeX` support, so you can always use that. See the `SageTeX` section of the Sage installation guide.

2.3 Using `TeXShop`

Starting with version 2.25, `TeXShop` includes support for `SageTeX`. If you move the file `sage.engine` from `~/Library/TeXShop/Engines/Inactive/Sage` to `~/Library/TeXShop/Engines` and put the line

```
%!TEX TS-program = sage
```

at the top of your document, then `TeXShop` will automatically run Sage for you when compiling your document.

Note that you will need to make sure that `LATEX` can find `sagetex.sty` using any of the methods above. You also might need to edit the `sage.engine` script to reflect the location of your Sage installation. `TeXShop` includes further documentation in the `~/Library/TeXShop/Engines/Inactive/Sage` folder; be sure to check out the “About Sage” PDF there, which has good advice on setting up things so that typesetting `SageTeX`-ified documents works automatically, and so that it continues to work when you upgrade your Sage installation.

2.4 Other scripts included with `SageTeX`

`SageTeX` includes several Python files which may be useful for working with “`SageTeX`-ified” documents. At this point they have likely bitrotted but are, for now, included for archaeological purposes.

The `remote-sagetex.py` script allows you to use `SageTeX` on a computer that doesn’t have Sage installed; see section 5 for more information.

Also included are `makestatic.py` and `extractsagecode.py`, which are convenience scripts that you can use after you’ve written your document. See section 4.7 and section 4.8 for information on using those scripts. The file `sagetexparse.py` is a module used by both those scripts. These three files are independent of `SageTeX`. If you install from a spkg, these scripts can be found in `$SAGE_ROOT/local/share/texmf/`.

3 Usage

Let's begin with a rough description of how **SageTeX** works. Naturally the very first step is to put `\usepackage{sagetex}` in the preamble of your document. When you use macros from this package and run **L^AT_EX** on your file, along with the usual zoo of auxiliary files, a `.sage` file is written with the same basename as your document. This is a Sage source file that uses the Python module from this package and when you run Sage on that file, it will produce a `.sout` and a `.scmd` file. The `.sout` file contains **L^AT_EX** code that, when you run **L^AT_EX** on your source file again, will pull in all the results of Sage's computation.

The `sagecommandline` environment additionally logs the plain sage commands and output furthermore in a `.scmd` file.

All you really need to know is that to typeset your document, you need to run **L^AT_EX**, then run Sage, then run **L^AT_EX** again.

Also keep in mind that everything you send to Sage is done within one Sage session. This means you can define variables and reuse them throughout your **L^AT_EX** document; if you tell Sage that `foo` is 12, then anytime afterwards you can use `foo` in your Sage code and Sage will remember that it's 12—just like in a regular Sage session.

Now that you know that, let's describe what macros **SageTeX** provides and how to use them. If you are the sort of person who can't be bothered to read documentation until something goes wrong, you can also just look through the `example.tex` file included with this package.¹

WARNING! When you run **L^AT_EX** on a file named `<filename>.tex`, the file `<filename>.sagetex.sage` is created—and will be *automatically overwritten* if it already exists. If you keep Sage scripts in the same directory as your SageTeX-ified **L^AT_EX** documents, use a different file name!

WARNING! Speaking of filenames, **SageTeX** really works best on files whose names don't have spaces or other “funny” characters in them. **SageTeX** *should* work on such files—and you should let us know if it doesn't—but it's safest to stick to files with alphanumeric characters and “safe” punctuation (i.e., nothing like `<`, `"`, `!`, `\`, or other characters that would confuse a shell).

The final option On a similar note, **SageTeX**, like many **L^AT_EX** packages, accepts the `final` option. When passed this option, either directly in the `\usepackage` line, or from the `\documentclass` line, **SageTeX** will not write a `.sage` file. It will try to read in the `.sout` file so that the **SageTeX** macros can pull in their results. However, this will not allow you to have an independent Sage script with the same basename as your document, since to get the `.sout` file, you need the `.sage` file.

¹Then again, if you're such a person, you're probably not reading this, and are already fiddling with `example.tex`...

3.1 Inline Sage

`\sage` `\sage{Sage code}` takes whatever Sage code you give it, runs Sage’s `latex` function on it, and puts the result into your document.

For example, if you do `\sage{matrix([[1, 2], [3,4]])^2}`, then that macro will get replaced by

```
\left(\begin{array}{rr}
7 & 10 \\
15 & 22
\end{array}\right)
```

in your document—that L^AT_EX code is exactly exactly what you get from doing

```
latex(matrix([[1, 2], [3,4]])^2)
```

in Sage.

Note that since L^AT_EX will do macro expansion on whatever you give to `\sage`, you can mix L^AT_EX variables and Sage variables! If you have defined the Sage variable `foo` to be 12 (using, say, the `sageblock` environment), then you can do something like this:

```
The prime factorization of the current page number plus foo
is $\sage{factor(foo + \thepage)}$.
```

Here, I’ll do just that right now: the prime factorization of the current page number plus 12 is `??`. (Wrong answer? See footnote.²) The `\sage` command doesn’t automatically use math mode for its output, so be sure to use dollar signs or a displayed math environment as appropriate.

`\sagestr` `\sagestr{Sage code}` is identical to `\sage`, but it does *not* run Sage’s `latex` function on the code you give it; it simply runs the Sage code and pulls the result into your L^AT_EX file. This is useful for calling functions that return L^AT_EX code; see the example file distributed along with SageT_EX for a demonstration of using this command to easily produce a table.

`\percent` If you are doing modular arithmetic or string formatting and need a percent sign in a call to `\sage` (or `\sageplot`), you can use `\percent`. Using a bare percent sign won’t work because L^AT_EX will think you’re starting a comment and get confused; prefixing the percent sign with a backslash won’t work because then “\” will be written to the `.sage` file and Sage will get confused. The `\percent` macro makes everyone happy.

²Is the above factorization wrong? If the current page number plus 12 is one larger than the claimed factorization, another Sage/L^AT_EX cycle on this source file should fix it. Why? The first time you run L^AT_EX on this file, the sine graph isn’t available, so the text where I’ve talked about the prime factorization is back one page. Then you run Sage, and it creates the sine graph and does the factorization. When you run L^AT_EX again, the sine graph pushes the text onto the next page, but it uses the Sage-computed value from the previous page. Meanwhile, the `.sage` file has been rewritten with the correct page number, so if you do another Sage/L^AT_EX cycle, you should get the correct value above. However, in some cases, even *that* doesn’t work because of some kind of T_EX weirdness in ending the one page a bit short and starting another.

Note that using `\percent` inside the verbatim-like environments described in section 3.3 isn't necessary; a literal “%” inside such an environment will get written, uh, verbatim to the `.sage` file.

Arguments with side effects Be careful when feeding `\sage` and `\sagestr` arguments that have side effects, since in some situations they can get evaluated more than once; see section 4.1.

3.2 Graphics and plotting

`\sageplot` `\sageplot[$\langle ltx\ opts \rangle$][$\langle fmt \rangle$]{ $\langle graphics\ obj \rangle$, $\langle keyword\ args \rangle$ }` plots the given Sage graphics object and runs an `\includegraphics` command to put it into your document. It does not have to actually be a plot of a function; it can be any Sage graphics object. The options are described in Table 1.

Option	Description
$\langle ltx\ options \rangle$	Any text here is passed directly into the optional arguments (between the square brackets) of an <code>\includegraphics</code> command.
$\langle fmt \rangle$	You can optionally specify a file extension here; Sage will then try to save the graphics object to a file with extension <i>fmt</i> . If not specified, SageTeX will save to EPS and PDF files; if saving to those formats does not work, SageTeX will save to a PNG file.
$\langle graphics\ obj \rangle$	A Sage object on which you can call <code>.save()</code> with a graphics filename.
$\langle keyword\ args \rangle$	Any keyword arguments you put here will all be put into the call to <code>.save()</code> .

Table 1: Explanation of options for the `\sageplot` command.

This setup allows you to control both the Sage side of things, and the \LaTeX side. For instance, the command

```
\sageplot[angle=30, width=5cm]{plot(sin(x), 0, pi), axes=False,
chocolate=True}
```

will run the following command in Sage:

```
sage: plot(sin(x), 0, pi).save(filename=autogen, axes=False,
chocolate=True)
```

Then, in your \LaTeX file, the following command will be issued automatically:

```
\includegraphics[angle=30, width=5cm]{autogen}
```


You can specify a file format if you like. This must be the *second* optional argument, so you must use empty brackets if you're not passing anything to `\includegraphics`:

```
\sageplot[] [png]{plot(sin(x), x, 0, pi)}
```

The filename is automatically generated, and unless you specify a format, both EPS and PDF files will be generated. This allows you to freely switch between using, say, a DVI viewer (many of which have support for automatic reloading, source specials and make the writing process easier) and creating PDFs for posting on the web or emailing to colleagues. SageTeX will fall back to creating a PNG file for any graphics object that cannot be saved as an EPS or PDF file; this is useful for three dimensional plot objects, which currently cannot be saved as EPS or PDF files.

If you ask for, say, a PNG file (or if one is automatically generated for you as described above), keep in mind that ordinary `latex` and DVI files have no support for PNG files; SageTeX detects this and will warn you that it cannot find a suitable file if using `latex`.³ If you use `pdflatex`, there will be no problems because PDF files can include PNG graphics.

When SageTeX cannot find a graphics file, it inserts this into your document:



That's supposed to resemble the image-not-found graphics used by web browsers and use the traditional “??” that L^AT_EX uses to indicate missing references.

You needn't worry about the filenames; they are automatically generated and will be put into the directory `sage-plots-for-filename.tex`. You can safely delete that directory anytime; if SageTeX can't find the files, it will warn you to run Sage to regenerate them.

WARNING! When you run Sage on your `.sage` file, all files in the `sage-plots-for-filename.tex` directory *will be deleted!* Do not put any files into that directory that you do not want to get automatically deleted.

The `epstopdf` option One of the graphics-related options supported by SageTeX is `epstopdf`. This option causes SageTeX to use the `epstopdf` command to convert EPS files into PDF files. Like with the `imagemagick` option, it doesn't check to see if the `epstopdf` command exists or add options: it just runs the command. This option was motivated by a bug in the matplotlib PDF backend which caused it to create invalid PDFs. Ideally, this option should never be necessary; if you do need to use it, file a bug!

This option will eventually be removed, so do not use it.

³We use a typewriter font here to indicate the executables which produce DVI and PDF files, respectively, as opposed to “L^AT_EX” which refers to the entire typesetting system.

3.2.1 3D plotting

Right now there is, to put it nicely, a bit of tension between the sort of graphics formats supported by `latex` and `pdflatex`, and the graphics formats supported by Sage’s 3D plotting systems. \LaTeX is happiest, and produces the best output, with EPS and PDF files, which are vector formats. Tachyon, Sage’s 3D plotting system, produces bitmap formats like BMP and PNG.

`SageTeX` will automatically fall back to saving plot objects in PNG format if saving to EPS and PDF fails, so it should automatically work with 3D plot objects. However, since `latex` does not support PNGs, when using 3D plotting (and therefore a bitmap format like PNG), `SageTeX` will always issue a warning about incompatible graphics if you use `latex`, provided you’ve processed the `.sage` file and the PNG file exists. The only exception is if you’re using the `imagemagick` option below.

The `imagemagick` option As a response to the above issue, the `SageTeX` package has an `imagemagick` option. If you specify this option in the preamble of your document with the usual “`\usepackage[imagemagick]{sagetex}`”, then when you are compiling your document using `latex`, any `\sageplot` command which requests a non-default format will cause the `SageTeX` Python script to convert the resulting file to EPS using the Imagemagick `convert` utility. It does this by executing “`convert filename.EXT filename.eps`” in a subshell. It doesn’t add any options, check to see if the `convert` command exists or belongs to Imagemagick—it just runs the command.

The resulting EPS files are not very high quality, but they will work. This option is not intended to produce good graphics, but to allow you to see your graphics when you use `latex` and DVI files while writing your document.

3.2.2 But that’s not good enough!

The `\sageplot` command tries to be both flexible and easy to use, but if you are just not happy with it, you can always do things manually: inside a `sagesilent` environment (see the next section) you could do

```
your special commands
x = your graphics object
x.save(filename=myspecialfile.ext, options, etc)
```

and then, in your source file, do your own `\includegraphics` command. The `SageTeX` package gives you full access to Sage and Python and doesn’t turn off anything in \LaTeX , so you can always do things manually.

3.3 Verbatim-like environments

The `SageTeX` package provides several environments for typesetting and executing blocks of Sage code.

sageblock Any text between `\begin{sageblock}` and `\end{sageblock}` will be typeset into your file, and also written into the `.sage` file for execution. This means you can do something like this:

```
\begin{sageblock}
  var('x')
  f(x) = sin(x) - 1
  g(x) = log(x)
  h(x) = diff(f(x) * g(x), x)
\end{sageblock}
```

and then anytime later write in your source file

```
We have  $h(2) = \text{\sage{h(2)}}$ , where  $h$  is the derivative of
the product of  $f$  and  $g$ .
```

and the `\sage` call will get correctly replaced by `??`. You can use any Sage or Python commands inside a `sageblock`; all the commands get sent directly to Sage.

sagesilent This environment is like `sageblock`, but it does not typeset any of the code; it just writes it to the `.sage` file. This is useful if you have to do some setup in Sage that is not interesting or relevant to the document you are writing.

sageverbatim This environment is the opposite of the one above: whatever you type will be typeset, but not written into the `.sage` file. This allows you to typeset pseudocode, code that will fail, or take too much time to execute, or whatever.

comment Logically, we now need an environment that neither typesets nor executes your Sage code...but the `verbatim` package, which is always loaded when using `SageTeX`, provides such an environment: `comment`. Another way to do this is to put stuff between `\iffalse` and `\fi`.

\sagetexindent There is one final bit to our verbatim-like environments: the indentation. The `SageTeX` package defines a length `\sagetexindent`, which controls how much the Sage code is indented when typeset. You can change this length however you like with `\setlength`: do `\setlength{\sagetexindent}{6ex}` or whatever.

sageexample This environment allow you to include doctest-like snippets in your document that will be nicely typeset. For example,

```
\begin{sageexample}
  sage: 1+1
  2
  sage: factor(x^2 + 2*x + 1)
  (x + 1)^2
\end{sageexample}
```

in your document will be typeset with the Sage inputs in the usual fixed-width font, and the outputs will be typeset as if given to a `\sage` macro, as you see

below: ??When typesetting the document, there is no test of the validity of the outputs (that is, typesetting with a typical L^AT_EX-Sage-L^AT_EX cycle does not do doctesting), but when using the `sageexample` environment, an extra file named “`myfile_doctest.sage`” is created with the contents of all those environments; it is formatted so that Sage can doctest that file. You should be able to doctest your document with “`sage -t myfile_doctest.sage`”. (This does not always work; if this fails for you, please contact the sage-support group.)

If you would like to see both the original text input and the typeset output, you can issue `\renewcommand{\sageexampleincludetextoutput}{True}` in your document. You can do the same thing with “False” to later turn it off. In the above example, this would cause SageT_EX to output both $(x + 1)^2$ and $(x + 1)^2$ in your typeset document.

Just as in doctests, multiline statements are acceptable. The only limitation is that triple-quoted strings delimited by “” cannot be used in a `sageexample` environment; instead, you can use triple-quoted strings delimited by ‘’.

See the `example.tex` file for many examples and more explanation.

The initial implementation of this environment is due to Nicolas M. Thiéry.

`sagecommandline`

This environment is similar to the `sageexample` environment in that it allow you to use SageT_EX as a pretty-printing command line, or to include doctest-like snippets in your document. The difference is that the output is typeset as text, much like running Sage on the command line, using the `lstlisting` environment. In particular, this environment provides Python syntax highlighting and line numbers. For example,

```
\begin{sagecommandline}
sage: 1+1
2
sage: factor(x^2 + 2*x + 1)
\end{sagecommandline}
```

becomes ??You have a choice of either explicitly providing the Sage output or leaving it up to the computer to fill in the blanks. Above, the output for `1 + 1` was provided, but the output for the `factor()` command wasn’t. Moreover, any Sage comment that starts with a “at” sign is escaped to L^AT_EX. In particular, you can use `\label` to mark line numbers in order to `\reference` and `\pagereference` them as usual. See the example file to see this mechanism in action.

If you prefer to typeset the output in L^AT_EX, you can set

```
\renewcommand{\sagecommandlinetextoutput}{False}
```

which produces ?? The Sage input and output is typeset using the `listings` package with the styles `SageInput` and `SageOutput`, respectively. If you don’t like the defaults you can change them. It is recommended to derive from `DefaultSageInput` and `DefaultSageOutput`, for example

```
\lstdefinestyle{SageInput}{style=DefaultSageInput,
basicstyle={\color{red}}}
```

```
\lstdefinestyle{SageOutput}{style=DefaultSageOutput,
                             basicstyle={\color{green}}}
```

makes things overly colorful: ??

3.4 Pausing SageTeX

Sometimes when you are writing a document, you may wish to temporarily turn off or pause SageTeX to concentrate more on your document than on the Sage computations, or to simply have your document typeset faster. You can do this with the following commands.

`\sagetexpause`
`\sagetexunpause`

Use these macros to “pause” and “unpause” SageTeX. After issuing this macro, SageTeX will simply skip over the corresponding calculations. Anywhere a `\sage` macro is used while paused, you will simply see “(SageTeX is paused)”, and anywhere a `\sageplot` macro is used, you will see:

SageTeX is paused; no graphic

Anything in the verbatim-like environments of section 3.3 will be typeset or not as usual, but none of the Sage code will be executed.

Obviously, you use `\sagetexunpause` to unpause SageTeX and return to the usual state of affairs. Both commands are idempotent; issuing them twice or more in a row is the same as issuing them once. This means you don’t need to precisely match pause and unpause commands: once paused, SageTeX stays paused until it sees `\sagetexunpause` and vice versa.

4 Other notes

Here are some other notes on using SageTeX.

4.1 Using the sage macro inside align (and similar) environments

The `align`, `align*`, and some other “fancy” math environments in the `amsmath` package do some special processing—in particular, they evaluate everything inside twice. This means that if you use `\sage` or `\sagestr` inside such an environment, it will be evaluated twice, and its argument will be put into the generated `.sage` file twice—and if that argument has side effects, those side effects will be executed twice! Doing something such as popping an element from a list will actually pop *two* elements and typeset the second. The solution is to do any processing that has side effects before the `align` environment (in a `sagesilent` environment, say) and to give `\sage` or `\sagestr` an argument with no side effects.

Thanks to Bruno Le Floch for reporting this.

4.2 Using sage inside caption

If you want to use `\sage` inside the `\caption` for a figure, you’ll need to prepend it with `\protect`, because (in \TeX parlance) the `\sage` macro is not “robust”. For example:

```
\caption{this figure illustrates why  $2 + 2 = \protect\sage{2 + 2}$ $.}
```

4.3 Using Sage \TeX with TeXworks

On Linux and OS X, it’s easy to get the \TeX works editor to work with Sage \TeX . You will define a new “typesetting engine” following these directions. First, in some convenient location, create a shell script with these contents:

```
#!/bin/sh
pdflatex $1.tex
sage $1.sagetex.sage
pdflatex $1.tex
```

Name it `sagetex-engine` or something similar. Then, in the Edit → Preferences menu, click the + button in the Processing tools section. Give the new tool a good name, like “Sage \TeX ”. In the Program space, browse to your script. Click the + for the Arguments and type `$basename` in the resulting box.

Then, back in your document, you should be able to select Sage \TeX in the typesetting engine dropdown menu and then typeset.

(You can also replace “`sage`” above with the `run-sagetex-if-necessary` script—see section 7.1.)

4.4 Using Beamer

The BEAMER package does not play nicely with verbatim-like environments unless you ask it to. To use code block environments in a BEAMER presentation, do:

```
\begin{frame}[fragile]
\begin{sageblock}
# sage stuff
# more stuff \end{sageblock}
\end{frame}
```

For some reason, BEAMER inserts an extra line break at the end of the environment; if you put the `\end{sageblock}` on the same line as the last line of your code, it works properly. See section 12.9, “Verbatim and Fragile Text”, in the BEAMER manual. (Thanks to Franco Saliola for reporting this.)

BEAMER’s overlays and `\sageplot` also need some help in order to work together, as discussed in this sage-support thread. If you want a plot to only appear in a certain overlay, you might try something like this in your frame:

```

\begin{itemize}
\item item 1
\item item 2
\item \sageplot[height=4cm][png]{(plot_slope_field(2*x,(x,-4,4),
(y,-4,4))+(x^2-2).plot(-2,2))}
\end{itemize}

```

but the plot will appear on all the overlays, instead of the third. The solution is to use the `\visible` macro:

```

\begin{itemize}
\item item 1
\item item 2
\item \visible<3->{\sageplot[height=4cm][png]{(plot_slope_field(2*x,(x,-4,4),
(y,-4,4))+(x^2-2).plot(-2,2))}}
\end{itemize}

```

Then the plot will only appear on the third (and later) overlays. (Thanks to Robert Mařík for this solution.)

4.5 Using the `rccol` package

If you are trying to use the `\sage` macro inside a table when using the `rccol` package, you need to use an extra pair of braces or typesetting will fail. That is, you need to do something like this:

```
abc & {\sage{foo.n()}} & {\sage{bar}} \\\
```

with each “`\sage{}`” enclosed in an extra `{}`. Thanks to Sette Diop for reporting this.

4.6 Plotting from Mathematica, Maple, etc.

Sage can use Mathematica, Maple, and friends and can tell them to do plotting, but since it cannot get those plots into a Sage graphics object, you cannot use `\sageplot` to use such graphics. You’ll need to use the method described in “But that’s not good enough!” (section 3.2.2) with some additional bits to get the directory right—otherwise your file will get saved to someplace in a hidden directory.

For Mathematica, you can do something like this inside a `sagesilent` or `sageblock` environment:

```

mathematica('myplot = commands to make your plot')
mathematica('Export["%s/graphicsfile.eps", myplot]' % os.getcwd())

```

then put `\includegraphics[opts]{graphicsfile}` in your file.

For Maple, you’ll need something like

```
maple('plotsetup(ps, plotoutput='%s/graphicsfile.eps', \
    plotoptions='whatever');' % os.getcwd())
maple('plot(function, x=1..whatever);')
```

and then `\includegraphics` as necessary.

These interfaces, especially when plotting, can be finicky. The above commands are just meant to be a starting point.

4.7 Sending SageTeX files to others who don't use Sage

4.7.1 The 21st century way

The SageMathCloud (cloud.sagemath.com) service has full support for SageTeX, is free to use, and has many fantastic collaboration features. If you somehow want to collaborate on a SageTeX-enabled TeXdocument with a colleague, using SageMathCloud is one of the best and easiest ways to do it. You and your collaborators simply create an account, then make a project for your collaboration, and add all the collaborators to the project. Then you can all enjoy realtime collaborative editing, PDF previews, chat, and more.

4.7.2 The N th century way, for $N < 21$

Using anything other than SageMathCloud, `git`, or similar tools these days seems pretty primitive. If emailing `.tex` files back and forth seems perfectly reasonable to you, or if you have to send a file to a journal, the easiest way is to simply include with your document the following files:

1. `sagetex.sty`
2. the generated `.sout` and `.scmd` files
3. the `sage-plots-for- $\langle filename \rangle$.tex` directory and its contents

As long as `sagetex.sty` is available, your document can be typeset using any reasonable L^AT_EX system. Since it is very common to include graphics files with a paper submission, this is a solution that should always work. (In particular, it will work with arXiv submissions.)

There is another option, and that is to use the `makestatic.py` script included with SageTeX. This script has been unmaintained for some time and likely won't work. If you want or need to use it and run into trouble, email the `sage-support` group and let us know.

Use of the script is quite simple. Copy it and `sagetexparse.py` to the directory with your document, and run

```
python makestatic.py inputfile [outputfile]
```

where `inputfile` is your document. (You can also set the executable bit of `makestatic.py` and use `./makestatic.py`.) This script needs the `pyparsing` module to be installed.⁴ You may optionally specify `outputfile`; if you do so, the

⁴If you don't have `pyparsing` installed, you can simply copy the file `$SAGE_ROOT/local/lib/python/matplotlib/pyparsing.py` into your directory.

results will be written to that file. If the file exists, it won't be overwritten unless you also specify the `-o` switch.

You will need to run this after you've compiled your document and run Sage on the `.sage` file. The script reads in the `.sout` file and replaces all the calls to `\sage` and `\sageplot` with their plain \LaTeX equivalent, and turns the `sageblock` and `sageverbatim` environments into `verbatim` environments. Any `sagesilent` environment is turned into a `comment` environment. Any `sagecommandline` environment is turned into a `lstlisting` environment, typesetting the relevant part of the `.scmd` file. The resulting document should compile to something identical, or very nearly so, to the original file.

One large limitation of this script is that it can't change anything while \SageTeX is paused, since Sage doesn't compute anything for such parts of your document. It also doesn't check to see if pause and unpause commands are inside comments or verbatim environments. If you're going to use `makestatic.py`, just remove all pause/unpause statements.

The parsing that `makestatic.py` does is pretty good, but not perfect. Right now it doesn't support having a comma-separated list of packages, so you can't have `\usepackage{sagetex, foo}`. You need to have just `\usepackage{sagetex}`. (Along with package options; those are handled correctly.) If you find other parsing errors, please let me know.

4.8 Extracting the Sage code from a document

(This script has the same unmaintained-and-probably-doesn't-work status as `makestatic.py`; see above.)

This next script is probably not so useful, but having done the above, this was pretty easy. The `extractsagecode.py` script does the opposite of `makestatic.py`, in some sense: given a document, it extracts all the Sage code and removes all the \LaTeX .

Its usage is the same as `makestatic.py`.

Note that the resulting file will almost certainly *not* be a runnable Sage script, since there might be \LaTeX commands in it, the indentation may not be correct, and the plot options just get written verbatim to the file. Nevertheless, it might be useful if you just want to look at the Sage code in a file.

5 Using \SageTeX without Sage installed

(This script has the same unmaintained-and-probably-doesn't-work status as `makestatic.py`; see above.)

You may want to edit and typeset a \SageTeX -ified file on a computer that doesn't have Sage installed. How can you do that? We need to somehow run Sage on the `.sage` file. The included script `remote-sagetex.py` takes advantage of Sage's network transparency and will use a remote server to do all the computations. Anywhere in this manual where you are told to "run Sage", instead of actually running Sage, you can run


```
python remote-sagetex.py filename.sage
```

The script will ask you for a server, username, and password, then process all your code and write a `.sout` file and graphics files exactly as if you had used a local copy of Sage to process the `.sage` script. (With some minor limitations and differences; see below.)

One important point: *the script requires Python 2.6*. It will not work with earlier versions. (It will work with Python 3.0 or later with some trivial changes.)

You can provide the server, username and password with the command-line switches `--server`, `--username`, and `--password`, or you can put that information into a file and use the `--file` switch to specify that file. The format of the file must be like the following:

```
# hash mark at beginning of line marks a comment
server = "http://example.com:1234"
username = 'my_user_name'
password = 's33krit'
```

As you can see, it's really just like assigning a string to a variable in Python. You can use single or double quotes and use hash marks to start comments. You can't have comments on the same line as an assignment, though. You can omit any of those pieces of information; the script will ask for anything it needs to know. Information provided as a command line switch takes precedence over anything found in the file.

You can keep this file separate from your L^AT_EX documents in a secure location; for example, on a USB thumb drive or in an automatically encrypted directory (like `~/Private` in Ubuntu). This makes it much harder to accidentally upload your private login information to the arXiv, put it on a website, send it to a colleague, or otherwise make your private information public.

5.1 Limitations of remote-sagetex.py

The `remote-sagetex.py` script has several limitations. It completely ignores the `epstopdf` and `imagemagick` flags. The `epstopdf` flag is not a big deal, since it was originally introduced to work around a matplotlib bug which has since been fixed. Not having `imagemagick` support means that you cannot automatically convert 3D graphics to eps format; using `pdflatex` to make PDFs works around this issue.

5.2 Other caveats

Right now, the “simple server API” that `remote-sagetex.py` uses is not terribly robust, and if you interrupt the script, it's possible to leave an idle session running on the server. If many idle sessions accumulate on the server, it can use up a lot of memory and cause the server to be slow, unresponsive, or maybe even crash. For now, I recommend that you only run the script manually. It's probably best to not configure your T_EX editing environment to automatically run `remote-sagetex.py`

whenever you typeset your document, at least not without showing you the output or alerting you about errors.

6 Implementation

There are two pieces to this package: a \LaTeX style file, and a Python module. They are mutually interdependent, so it makes sense to document them both here.

6.1 The style file

All macros and counters intended for use internal to this package begin with “ST@”.

6.1.1 Initialization

Let’s begin by loading some packages. The key bits of `sageblock` and friends are `stol—um`, adapted from the `verbatim` package manual. So grab the `verbatim` package. We also need the `fancyvrb` package for the `sageexample` environment

```

1 \RequirePackage{verbatim}
2 \RequirePackage{fancyvrb}
and listings for the sagecommandline environment.
3 \RequirePackage{listings}
4 \RequirePackage{color}
5 \lstdefinlanguage{Sage}[] {Python}
6 {morekeywords={False,sage,True},sensitive=true}
7 \lstdefinlanguage{SageOutput}[] {}
8 {morekeywords={False,True},sensitive=true}
9 \lstdefinestyle{DefaultSageInputOutput}{
10 nolol,
11 identifierstyle=,
12 name=sagecommandline,
13 xleftmargin=5pt,
14 numbersep=5pt,
15 aboveskip=0pt,
16 belowskip=0pt,
17 breaklines=true,
18 numberstyle=\footnotesize,
19 numbers=right
20 }
21 \lstdefinestyle{DefaultSageInput}{
22 language=Sage,
23 style=DefaultSageInputOutput,
24 basicstyle={\ttfamily\bfseries},
25 commentstyle={\ttfamily\color{dgreencolor}},
26 keywordstyle={\ttfamily\color{dbluecolor}\bfseries},
27 stringstyle={\ttfamily\color{dgraycolor}\bfseries},
28 }
29 \lstdefinestyle{DefaultSageOutput}{

```

```

30 language=SageOutput,
31 style=DefaultSageInputOutput,
32 basicstyle=\ttfamily,
33 commentstyle=\ttfamily\color{dgreencolor}},
34 keywordstyle=\ttfamily\color{dbluecolor}},
35 stringstyle=\ttfamily\color{dgraycolor}},
36 }
37 \lstdefinestyle{SageInput}{
38   style=DefaultSageInput,
39 }
40 \lstdefinestyle{SageOutput}{
41   style=DefaultSageOutput,
42 }
43 \definecolor{dbluecolor}{rgb}{0.01,0.02,0.7}
44 \definecolor{dgreencolor}{rgb}{0.2,0.4,0.0}
45 \definecolor{dgraycolor}{rgb}{0.30,0.3,0.30}

```

Unsurprisingly, the `\sageplot` command works poorly without graphics support.

```
46 \RequirePackage{graphicx}
```

The `makecmds` package gives us a `\provideenvironment` which we need, and we use `ifpdf` and `ifthen` in `\sageplot` so we know what kind of files to look for. Since `ifpdf` doesn't detect running under XeTeX (which defaults to producing PDFs), we need `ifxetex`. Hopefully the `ifpdf` package will get support for this and we can drop `ifxetex`. We also work around ancient TeX distributions that don't have `ifxetex` and assume that they don't have XeTeX.

```

47 \RequirePackage{makecmds}
48 \RequirePackage{ifpdf}
49 \RequirePackage{ifthen}
50 \IfFileExists{ifxetex.sty}{
51   \RequirePackage{ifxetex}
52 }{
53   \newboolean{xetex}
54   \setboolean{xetex}{false}}

```

Next set up the counters, default indent, and flags.

```

55 \newcounter{ST@inline}
56 \newcounter{ST@plot}
57 \newcounter{ST@cmdline}
58 \setcounter{ST@inline}{0}
59 \setcounter{ST@plot}{0}
60 \setcounter{ST@cmdline}{0}
61 \newlength{\sagetexindent}
62 \setlength{\sagetexindent}{5ex}
63 \newif\ifST@paused
64 \ST@pausedfalse

```

Set up the file stuff, which will get run at the beginning of the document, after we know what's happening with the `final` option. First, we open the `.sage` file:

```

65 \AtBeginDocument{\@ifundefined{ST@final}{%
66 \newwrite\ST@sf%

```

```

67 \immediate\openout\ST@sf=\jobname.sagetex.sage%

\ST@wsf We will write a lot of stuff to that file, so make a convenient abbreviation, then
use it to put the initial commands into the .sage file. The hash mark below gets
doubled when written to the file, for some obscure reason related to parameter
expansion. It's valid Python, though, so I haven't bothered figuring out how to
get a single hash. We are assuming that the extension is .tex; see the initplot
documentation on page 33 for discussion of file extensions. (There is now the
currfile package (http://www.ctan.org/pkg/currfile/) which can figure out
file extensions, apparently.) The “(\jobname.sagetex.sage)” business is there
because the comment below will get pulled into the autogenerated .py file (second
order autogeneration!) and I'd like to reduce possible confusion if someone is
looking around in those files. Finally, we check for version mismatch and bail if
the .py and .sty versions don't match and the user hasn't disabled checking. Note
that we use ^^J and not ^^J% when we need indented lines. Also, sagetex.py
now includes a version variable which eliminates all the irritating string munging
below, and later we can remove this stuff and just use sagetex.version.

68 \newcommand{\ST@wsf}[1]{\immediate\write\ST@sf{#1}}%
69 \ST@wsf{%
70 # -*- encoding: utf-8 -*-^^J%
71 # This file (\jobname.sagetex.sage) was *autogenerated* from \jobname.tex with
72 sagetex.sty version \ST@ver.^^J%
73 import sagetex^^J%
74 _st_ = sagetex.SageTeXProcessor('\jobname', version='\ST@ver', version_check=\ST@versioncheck)}%
On the other hand, if the ST@final flag is set, don't bother with any of the file
stuff, and make \ST@wsf a no-op.

75 {\newcommand{\ST@wsf}[1]{\relax}}

\ST@dodfsetup The sageexample environment writes stuff out to a different file formatted so that
one can run doctests on it. We define a macro that only sets this up if necessary.

76 \newcommand{\ST@dodfsetup}{%
77 \@ifundefined{ST@diddfsetup}{%
78 \newwrite\ST@df%
79 \immediate\openout\ST@df=\jobname_doctest.sage%
80 \immediate\write\ST@df{r"^^J%
81 This file was *autogenerated* from \jobname.tex with sagetex.sty^^J%
82 version \ST@ver. It contains the contents of all the^^J%
83 sageexample environments from \jobname.tex. You should be able to^^J%
84 doctest this file with "sage -t \jobname_doctest.sage".^^J%
85 ^^J%
86 It is always safe to delete this file; it is not used in typesetting your^^J%
87 document.^^J}%
88 \AtEndDocument{\immediate\write\ST@df{""}}%
89 \gdef\ST@diddfsetup{x}}%
90 {\relax}}

\ST@wdf This is the companion to \ST@wsf; it writes to the doctest file, assuming that

```

is has been set up. We ignore the `final` option here since nothing in this file is relevant to typesetting the document.

```
91 \newcommand{\ST@wdf}[1]{\immediate\write\ST@df{#1}}
```

Now we declare our options, which mostly just set flags that we check at the beginning of the document, and when running the `.sage` file.

The `final` option controls whether or not we write the `.sage` file; the `imagemagick` and `epstopdf` options both want to write something to that same file. So we put off all the actual file stuff until the beginning of the document—by that time, we’ll have processed the `final` option (or not) and can check the `\ST@final` flag to see what to do. (We must do this because we can’t specify code that runs if an option *isn’t* defined.)

For `final`, we set a flag for other guys to check, and if there’s no `.sout` file, we warn the user that something fishy is going on.

```
92 \DeclareOption{final}{%
93   \newcommand{\ST@final}{x}%
94   \IfFileExists{\jobname.sagetex.sout}{\AtEndDocument{\PackageWarningNoLine{sagetex}%
95     {'final' option provided, but \jobname.sagetex.sout^^Jdoesn't exist! No Sage
96     input will appear in your document. Remove the 'final'^^Joption and
97     rerun LaTeX on your document}}}}
```

For `imagemagick`, we set two flags: one for L^AT_EX and one for Sage. It’s important that we set `ST@useimagemagick` *before* the beginning of the document, so that the graphics commands can check that. We do wait until the beginning of the document to do file writing stuff.

```
98 \DeclareOption{imagemagick}{%
99   \newcommand{\ST@useimagemagick}{x}%
100   \AtBeginDocument{%
101     \ifundefined{ST@final}{%
102       \ST@wsf{_st_.useimagemagick = True}}{}}}
```

For `epstopdf`, we just set a flag for Sage.

```
103 \DeclareOption{epstopdf}{%
104   \AtBeginDocument{%
105     \ifundefined{ST@final}{%
106       \ST@wsf{_st_.useepstopdf = True}}{}}}
```

By default, we check to see if the `.py` and `.sty` file versions match. But we let the user disable this.

```
107 \newcommand{\ST@versioncheck}{True}
108 \DeclareOption{noversioncheck}{%
109   \renewcommand{\ST@versioncheck}{False}}
110 \ProcessOptions\relax
```

The `\relax` is a little incantation suggested by the “L^AT_EX 2_ε for class and package writers” manual, section 4.7.

Pull in the `.sout` file if it exists, or do nothing if it doesn’t. I suppose we could do this inside an `AtBeginDocument` but I don’t see any particular reason to do that. It will work whenever we load it. If the `.sout` file isn’t found, print the

usual \TeX -style message. This allows programs (`Latexmk`, for example) that read the `.log` file or terminal output to detect the need for another typesetting run to do so. If the “No file `foo.sout`” line doesn’t work for some software package, please let me know and I can change it to use `PackageInfo` or whatever.

```
111 \InputIfFileExists{\jobname.sagetex.sout}{%
112 {\typeout{No file \jobname.sagetex.sout.}}
```

The user might load the `hyperref` package after this one (indeed, the `hyperref` documentation insists that it be loaded last) or not at all—so when we hit the beginning of the document, provide a dummy `NoHyper` environment if one hasn’t been defined by the `hyperref` package. We need this for the `\sage` macro below.

```
113 \AtBeginDocument{\provideenvironment{NoHyper}}{}}
```

6.1.2 The `\sage` and `\sagestr` macros

\ST@sage This macro combines `\ref`, `\label`, and Sage all at once. First, we use Sage to get a \LaTeX representation of whatever you give this function. The Sage script writes a `\newlabel` line into the `.sout` file, and we read the output using the `\ref` command. Usually, `\ref` pulls in a section or theorem number, but it will pull in arbitrary text just as well.

The first thing it does it write its argument into the `.sage` file, along with a counter so we can produce a unique label. We wrap a try/except around the function call so that we can provide a more helpful error message in case something goes wrong. (In particular, we can tell the user which line of the `.tex` file contains the offending code.) Note the difference between `^^J` and `^^J%`: the newline immediately after the former puts a space into the output, and the percent sign in the latter suppresses this.

```
114 \newcommand{\ST@sage}[1]{\ST@wsf{%
115 try:^^J
116 _st_.current_tex_line = \the\inputlineno^^J
117 _st_.inline(\theST@inline, #1)^^J%
118 except:^^J
119 _st_.goboom(\the\inputlineno)}}%
```

The `inline` function of the Python module is documented on page 34. Back in \LaTeX -land: if paused, say so.

```
120 \ifST@paused
121 \mbox{(Sage\TeX{} is paused)}}%
```

Otherwise...our use of `\newlabel` and `\ref` seems awfully clever until you load the `hyperref` package, which gleefully tries to hyperlink the hell out of everything. This is great until it hits one of our special `\newlabels` and gets deeply confused. Fortunately the `hyperref` folks are willing to accomodate people like us, and give us a `NoHyper` environment.

```
122 \else
123 \begin{NoHyper}\ref{@sageinline\theST@inline}\end{NoHyper}%
```

Now check if the label has already been defined. (The internal implementation of labels in \LaTeX involves defining a macro called “`r@@labelname`”.) If it hasn’t, we

set a flag so that we can tell the user to run Sage on the `.sage` file at the end of the run.

```
124 \@ifundefined{r@@sageinline\theST@inline}{\gdef\ST@rerun{x}}{}%
125 \fi
```

In any case, the last thing to do is step the counter.

```
126 \stepcounter{ST@inline}}
```

`\sage` This is the user-visible macro; it runs Sage’s `latex()` on its argument.

```
127 \newcommand{\sage}[1]{\ST@sage{latex(#1)}}
```

`\sagestr` Like above, but doesn’t run `latex()` on its argument.

```
128 \newcommand{\sagestr}[1]{\ST@sage{#1}}
```

`\percent` A macro that inserts a percent sign. This is more-or-less stolen from the Docstrip manual; there they change the catcode inside a group and use `\gdef`, but here we try to be more `LATEX` and use `\newcommand`.

```
129 \catcode'\%=12
130 \newcommand{\percent}{%}
131 \catcode'\%=14
```

6.1.3 The `\sageplot` macro and friends

Plotting is rather more complicated, and requires several helper macros that accompany `\sageplot`.

`\ST@plotdir` A little abbreviation for the plot directory. We don’t use `\graphicspath` because it’s apparently slow—also, since we know right where our plots are going, no need to have `LATEX` looking for them.

```
132 \newcommand{\ST@plotdir}{sage-plots-for-\jobname.tex}
```

`\ST@missingfilebox` The code that makes the “file not found” box. This shows up in a couple places below, so let’s just define it once.

```
133 \newcommand{\ST@missingfilebox}{\framebox[2cm]{\rule[-1cm]{0cm}{2cm}\textbf{???}}}
```

`\sageplot` This function is similar to `\sage`. The neat thing that we take advantage of is that commas aren’t special for arguments to `LATEX` commands, so it’s easy to capture a bunch of keyword arguments that get passed right into a Python function.

This macro has two optional arguments, which can’t be defined using `LATEX`’s `\newcommand`; we use Scott Pakin’s brilliant `newcommand` package to create this macro; the options I fed to his script were similar to this:

```
MACRO sageplot OPT[#1={width}] OPT[#2={notprovided}] #3
```

Observe that we are using a Python script to write `LATEX` code which writes Python code which writes `LATEX` code. Crazy!

Here’s the wrapper command which does whatever magic we need to get two optional arguments.

```
134 \newcommand{\sageplot}[1] [] {%
135 \@ifnextchar[{\ST@sageplot[#1]}{\ST@sageplot[#1] [notprovided]}}
```




Figure 1: The logic tree that `\sageplot` uses to decide whether to run `\includegraphics` or to yell at the user. “Format” is the #2 argument to `\sageplot`, “STig ext” means a call to `\ST@inclgrfx` with “ext” as the second argument, and “IM” is Imagemagick.

The first optional argument #1 will get shoved right into the optional argument for `\includegraphics`, so the user has easy control over the L^AT_EX aspects of the plotting. (Perhaps a future version of SageT_EX will allow the user to specify in the package options a set of default options to be used throughout.) The second optional argument #2 is the file format and allows us to tell what files to look for. It defaults to “notprovided”, which tells the Python module to create EPS and PDF files. Everything in #3 gets put into the Python function call, so the user can put in keyword arguments there which get interpreted correctly by Python.

`\ST@sageplot` Let’s see the real code here. We write a couple lines to the `.sage` file, including a counter, input line number, and all of the mandatory argument; all this is wrapped in another try/except.

```

136 \def\ST@sageplot[#1][#2]#3{\ST@wsf{try:^^J
137 _st_.current_tex_line = \the\inputlineno^^J
138 _st_.plot(\theST@plot, format='#2', _p_=#3)^^Jexcept:^^J
139 _st_.goboom(\the\inputlineno)}%

```

The Python `plot` function is documented on page 39.

Now we include the appropriate graphics file. Because the user might be producing DVI or PDF files, and have supplied a file format or not, and so on, the logic we follow is a bit complicated. Figure 1 shows what we do; for completeness—and because I think drawing trees with TikZ is really cool—we show what `\ST@inclgrfx` does in Figure 2. This entire complicated business is intended to avoid doing an `\includegraphics` command on a file that doesn’t exist, and to issue warnings appropriate to the situation.

If we are creating a PDF, we check to see if the user asked for a different format, and use that if necessary:

```

140 \ifthenelse{\boolean{pdf} \or \boolean{xetex}}{

```



```

141 \ifthenelse{\equal{#2}{notprovided}}{%
142   {\ST@inclgrfx{#1}{pdf}}%
143   {\ST@inclgrfx{#1}{#2}}}

```

Otherwise, we are creating a DVI file, which only supports EPS. If the user provided a format anyway, don't include the file (since it won't work) and warn the user about this. (Unless the file doesn't exist, in which case we do the same thing that \ST@inclgrfx does.)

```

144 { \ifthenelse{\equal{#2}{notprovided}}{%
145   {\ST@inclgrfx{#1}{eps}}%

```

If a format is provided, we check to see if we're using the imagemagick option. If not, we're going to issue some sort of warning, depending on whether the file exists yet or not.

```

146   {\@ifundefined{ST@useimagemagick}%
147     {\IfFileExists{\ST@plotdir/plot-\theST@plot.#2}%
148       {\ST@missingfilebox%
149         \PackageWarning{sagetex}{Graphics file
150           \ST@plotdir/plot-\theST@plot.#2\space on page \thepage\space
151           cannot be used with DVI output. Use pdflatex or create an EPS
152           file. Plot command is}}%
153       {\ST@missingfilebox%
154         \PackageWarning{sagetex}{Graphics file
155           \ST@plotdir/plot-\theST@plot.#2\space on page \thepage\space
156           does not exist. Plot command is}}%
157       \gdef\ST@rerun{x}}}%

```

Otherwise, we are using Imagemagick, so try to include an EPS file anyway.

```

158   {\ST@inclgrfx{#1}{eps}}}%

```

Step the counter and we're done with the usual work.

```

159 \stepcounter{ST@plot}}

```

\ST@inclgrfx This command includes the requested graphics file (#2 is the extension) with the requested options (#1) if the file exists. Note that it just needs to know the extension, since we use a counter for the filename. If we are paused, it just puts in a little box saying so.

```

160 \newcommand{\ST@inclgrfx}[2]{\ifST@paused
161   \fbox{\rule[-1cm]{0cm}{2cm}Sage\TeX{} is paused; no graphic}
162 \else
163   \IfFileExists{\ST@plotdir/plot-\theST@plot.#2}%
164     {\includegraphics[#1]{\ST@plotdir/plot-\theST@plot.#2}}%

```

If the file doesn't exist, we try one more thing before giving up: the Python module will automatically fall back to saving as a PNG file if saving as an EPS or PDF file fails. So if making a PDF, we look for a PNG file.

If the file isn't there, we insert a little box to indicate it wasn't found, issue a warning that we didn't find a graphics file, then set a flag that, at the end of the run, tells the user to run Sage again.

```

165   {\IfFileExists{\ST@plotdir/plot-\theST@plot.png}%

```




Figure 2: The logic used by the `\ST@inclgrfx` command.

```

166     {\ifpdf
167       \ST@inclgrfx{#1}{png}
168     \else
169       \PackageWarning{sagetex}{Graphics file
170         \ST@plotdir/plot-\theST@plot.png on page \thepage\space not
171         supported; try using pdflatex. Plot command is}%
172       \fi}%
173     {\ST@missingfilebox%
174       \PackageWarning{sagetex}{Graphics file
175         \ST@plotdir/plot-\theST@plot.#2\space on page \thepage\space does not
176         exist. Plot command is}%
177       \gdef\ST@rerun{x}}
178 \fi}

```

Figure 2 makes this a bit clearer.

6.1.4 Verbatim-like environments

`\ST@beginsfbl` This is “begin .sage file block”, an internal-use abbreviation that sets things up when we start writing a chunk of Sage code to the .sage file. It begins with some \TeX magic that fixes spacing, then puts the start of a try/except block in the .sage file—this not only allows the user to indent code without Sage/Python complaining about indentation, but lets us tell the user where things went wrong. The `blockbegin` and `blockend` functions are documented on page 35. The last bit is some magic from the `verbatim` package manual that makes \LaTeX respect line breaks.

```

179 \newcommand{\ST@beginsfbl}{%

```

```

180 \@bsphack\ST@wsf{%
181 _st_.current_tex_line = \the\inputlineno^^J%
182 _st_.blockbegin()^^Jtry:}%
183 \let\do\@makeother\dospecials\catcode'\^^M\active}

\ST@endsfbl The companion to \ST@beginsfbl.
184 \newcommand{\ST@endsfbl}{%
185 \ST@wsf{except:^^J
186 _st_.goboom(\the\inputlineno)^^J_st_.blockend()}}

Now let's define the “verbatim-like” environments. There are four possibilities,
corresponding to the two independent choices of typesetting the code or not, and
writing to the .sage file or not.

sageblock This environment does both: it typesets your code and puts it into the .sage file
for execution by Sage.
187 \newenvironment{sageblock}{\ST@beginsfbl%
The space between \ST@wsf{ and \the is crucial! It, along with the “try:”, is
what allows the user to indent code if they like. This line sends stuff to the .sage
file.
188 \def\verbatim@processline{\ST@wsf{ \the\verbatim@line}%
Next, we typeset your code and start the verbatim environment.
189 \hspace{\sagetexindent}\the\verbatim@line\par}%
190 \verbatim}%

At the end of the environment, we put a chunk into the .sage file and stop the
verbatim environment.
191 {\ST@endsfbl\endverbatim}

sagesilent This is from the verbatim package manual. It's just like the above, except we
don't typeset anything.
192 \newenvironment{sagesilent}{\ST@beginsfbl%
193 \def\verbatim@processline{\ST@wsf{ \the\verbatim@line}}%
194 \verbatim@start}%
195 {\ST@endsfbl\@esphack}

sageverbatim The opposite of sagesilent. This is exactly the same as the verbatim environ-
ment, except that we include some indentation to be consistent with other typeset
Sage code.
196 \newenvironment{sageverbatim}{%
197 \def\verbatim@processline{\hspace{\sagetexindent}\the\verbatim@line\par}%
198 \verbatim}%
199 {\endverbatim}

```

Logically, we now need an environment which neither typesets *nor* writes code to the .sage file. The verbatim package's `comment` environment does that.

`sageexample` Finally, we have an environment which is mostly-but-not-entirely verbatim; this is the `example` environment, which takes input like Sage doctests, and prints out the commands verbatim but nicely typesets the output of those commands. This and the corresponding Python function are originally due to Nicolas M. Thiéry.

```

200 \newcommand{\sageexampleincludetextoutput}{False}
201 \newenvironment{sageexample}{%
202   \ST@wsf{%
203 try:^^J
204 _st_.current_tex_line = \the\inputlineno^^J
205 _st_.doctest(\theST@inline, r"")%
206   \ST@dodfsetup%
207   \ST@wdf{Sage example, line \the\inputlineno:^^J}%
208   \begingroup%
209   \@bsphack%
210   \let\do\@makeother\dospecials%
211   \catcode'\^^M\active%
212   \def\verbatim@processline{%
213     \ST@wsf{\the\verbatim@line}%
214     \ST@wdf{\the\verbatim@line}%
215   }%
216   \verbatim@start%
217 }
218 {
219   \@esphack%
220   \endgroup%
221   \ST@wsf{%
222     "", globals(), locals(), \sageexampleincludetextoutput)^^Jexcept:^^J
223     _st_.goboom(\the\inputlineno)}%
224   \ifST@paused%
225     \mbox{(Sage\TeX{} is paused)}%
226   \else%
227     \begin{NoHyper}\ref{@sageinline\theST@inline}\end{NoHyper}%
228     \ifundefined{r@@sageinline\theST@inline}{\gdef\ST@rerun{x}}{}%
229   \fi%
230   \ST@wdf{}%
231   \stepcounter{ST@inline}}

```

`sagecommandline` This environment is similar to the `sageexample` environment, but typesets the Sage output as text with Python syntax highlighting.

```

232 \newcommand{\sagecommandlinetextoutput}{True}
233 \newlength{\sagecommandlineskip}
234 \setlength{\sagecommandlineskip}{8pt}
235 \newenvironment{sagecommandline}{%
236   \ST@wsf{%
237 try:^^J
238 _st_.current_tex_line = \the\inputlineno^^J
239 _st_.commandline(\theST@cmdline, r"")%
240   \ST@dodfsetup%
241   \ST@wdf{Sage commandline, line \the\inputlineno:^^J}%

```

```

242 \begingroup%
243 \@bsphack%
244 \let\do\@makeother\dospecials%
245 \catcode'\^M\active%
246 \def\verbatim@processline{%
247   \ST@wsf{\the\verbatim@line}%
248   \ST@wdf{\the\verbatim@line}%
249 }%
250 \verbatim@start%
251 }
252 {
253   \@esphack%
254   \endgroup%
255   \ST@wsf{%
256     "", globals(), locals(), \sagecommandlinetextoutput)^Jexcept:^J
257     _st_.goboom(\the\inputlineno)}%
258   \ifST@paused%
259     \mbox{(Sage\TeX{} is paused)}%
260   \else%
261     \begin{NoHyper}\ref{@sagecmdline\theST@cmdline}\end{NoHyper}%
262     \@ifundefined{r@sagecmdline\theST@cmdline}{\gdef\ST@rerun{x}}{}%
263   \fi%
264   \ST@wdf{}%
265   \stepcounter{ST@cmdline}}

```

6.1.5 Pausing SageTeX

How can one have Sage to stop processing SageTeX output for a little while, and then start again? At first I thought I would need some sort of “goto” statement in Python, but later realized that there’s a dead simple solution: write triple quotes to the `.sage` file to comment out the code. Okay, so this isn’t *really* commenting out the code; PEP 8 says block comments should use “#” and Sage will read in the “commented-out” code as a string literal. For the purposes of SageTeX, I think this is a good decision, though, since (1) the pausing mechanism is orthogonal to everything else, which makes it easier to not screw up other code, and (2) it will always work.

This illustrates what I really like about SageTeX: it mixes L^AT_EX and Sage/Python, and often what is difficult or impossible in one system is trivial in the other.

sagetexpause This macro pauses SageTeX by effectively commenting out code in the `.sage` file. When running the corresponding `.sage` file, Sage will skip over any commands issued while SageTeX is paused.

```

266 \newcommand{\sagetexpause}{\ifST@paused\relax\else
267 \ST@wsf{print 'SageTeX paused on \jobname.tex line \the\inputlineno'^J"""}
268 \ST@pausedtrue
269 \fi}

```

`sagetexunpause` This is the obvious companion to `\sagetexpause`.

```
270 \newcommand{\sagetexunpause}{\ifST@paused
271 \ST@wsf{"""^Jprint 'SageTeX unpaused on \jobname.tex line \the\inputlineno'}
272 \ST@pausedfalse
273 \fi}
```

6.1.6 End-of-document cleanup

We tell the Sage script to write some information to the `.sout` file, then check to see if `ST@rerun` ever got defined. If not, all the inline formulas and plots worked, so do nothing. We check to see if we're paused first, so that we can finish the triple-quoted string in the `.sage` file.

```
274 \AtEndDocument{\ifST@paused
275 \ST@wsf{"""^Jprint 'SageTeX unpaused at end of \jobname.tex'}
276 \fi
277 \ST@wsf{_st_.endofdoc()}%
278 \@ifundefined{ST@rerun}{}%
```

Otherwise, we issue a warning to tell the user to run Sage on the `.sage` file. Part of the reason we do this is that, by using `\ref` to pull in the inlines, \LaTeX will complain about undefined references if you haven't run the Sage script—and for many \LaTeX users, myself included, the warning “there were undefined references” is a signal to run \LaTeX again. But to fix these particular undefined references, you need to run *Sage*. We also suppress file-not-found errors for graphics files, and need to tell the user what to do about that.

At any rate, we tell the user to run Sage if it's necessary.

```
279 {\typeout{*****}}
280 \PackageWarningNoLine{sagetex}{there were undefined Sage formulas and/or
281 plots.^JRun Sage on \jobname.sagetex.sage, and then run LaTeX on \jobname.tex
282 again}}
283 \typeout{*****}}
```

6.2 The Python module

The style file writes things to the `.sage` file and reads them from the `.sout` file. The Python module provides functions that help produce the `.sout` file from the `.sage` file.

A note on Python and Docstrip There is one tiny potential source of confusion when documenting Python code with Docstrip: the percent sign. If you have a long line of Python code which includes a percent sign for string formatting and you break the line with a backslash and begin the next line with a percent sign, that line *will not* be written to the output file. This is only a problem if you *begin* the line with a (single) percent sign; there are no troubles otherwise.

On to the code. Munge the version string (which we get from `sagetex.dtx`) to extract what we want, then import what we need:

```

284 pyversion = ' '.join(__version__.strip(' ').split()[0:2])
285 from sage.misc.latex import latex
286 from sage.repl.preparse import preparse
287 import sys
288 import os
289 import os.path
290 import hashlib
291 import traceback
292 import subprocess
293 import shutil
294 import re
295 from collections import defaultdict

```

Define an exception class for version mismatches. I suppose I could just use `ValueError`, but this is easy enough:

```

296 class VersionError(Exception):
297     pass

```

Sometimes our macros that write things to the `.sout` file get evaluated twice, most commonly in the “fancy” AMS environments such as `align` and `multline`. So we need to keep track of the counters we’ve seen so we don’t write labels to the `.sout` file more than once. We have more than one kind of label, so a dictionary is the natural way to store the counters we’ve seen for each kind of label. For convenience let’s make a dictionary subclass for which (1) values default to `-1`, and (2) there’s an `increment(key)` function that just increments the value corresponding to the key.

```

298 class MyDict(defaultdict):
299     def __init__(self, *args, **kwargs):
300         defaultdict.__init__(self, *args, **kwargs)
301         self.default_factory = lambda: -1
302
303     def increment(self, key):
304         self[key] = self[key] + 1

```

Here’s a helper function used by `doctest`; it works like `j.join(xs)`, but ensures exactly one copy of `j` between the strings in `xs`. Intended for `j` to be a single character, particularly newline so that you can join things with no extra blank lines.

```

305 def joinone(j, xs_):
306     if len(xs_) >= 2:
307         xs = ([xs_[0].rstrip(j)] +
308              [x.strip(j) for x in xs_[1:-1]] +
309              [xs_[-1].lstrip(j)])
310     else:
311         xs = xs_
312     return j.join(xs)

```

Another helper, used by `commandline` (and maybe, someday, `doctest`?). In each line, we look for a possibly empty sequence of spaces followed by a non-whitespace character, so we can distinguish between whitespace-only lines (which we ignore) and lines that have no leading spaces.

One tiny possible problem: you might have a line of only, say, two spaces, but perhaps the “real” lines all start with at least three spaces. Then you would, for that line, do `line[2:]`. That seems like it might raise an error, since the line only has indices 0 and 1, but Python’s indexing handles this perfectly: in that case, `line[2:]` will be the empty string, which is fine for our purposes.

```

313 def strip_common_leading_spaces(s):
314     lines = s.splitlines()
315     lead = min(m.end() for m in
316               [re.match(' *\S', line) for line in lines]
317               if m is not None) - 1
318     return '\n'.join(line[lead:] for line in lines)

```

6.2.1 The SageTeXProcessor class

The star of the show, as it were. We define a `SageTeXProcessor` class so that it’s a bit easier to carry around internal state. We used to just have some global variables and a bunch of functions, but this seems a bit nicer and easier.

```

319 class SageTeXProcessor():

```

If the original `.tex` file has spaces in its name, the `\jobname` we get is surrounded by double quotes, so fix that. Technically, it is possible to have double quotes in a legitimate filename, but dealing with that sort of quoting is unpleasant. And yes, we’re ignoring the possibility of tabs and other whitespace in the filename. Patches for handling pathological filenames welcome.

```

320 def __init__(self, jobname, version=None, version_check=True):
321     if version != pyversion:
322         errstr = """versions of .sty and .py files do not match.
323 {0}.sagetex.sage was generated by sagetex.sty version "{1}", but
324 is being processed by sagetex.py version "{2}".
325 Please make sure that TeX is using the sagetex.sty
326 from your current version of Sage; see
327 http://www.sagemath.org/doc/installation/sagetex.html.""".format(jobname,
328 version, pyversion)
329         if version_check:
330             raise VersionError, errstr
331         else:
332             print '**** WARNING! Skipping version check for .sty and .py files, and'
333             print errstr
334     if ' ' in jobname:
335         jobname = jobname.strip(' ')
336     self.progress('Processing Sage code for {0}.tex...'.format(jobname))
337     self.didinitplot = False
338     self.useimagemagick = False
339     self.useepstopdf = False
340     self.plotdir = 'sage-plots-for-' + jobname + '.tex'
341     self.filename = jobname
342     self.name = os.path.splitext(jobname)[0]
343     autogenstr = """% This file was *autogenerated* from {0}.sagetex.sage with
344 % sagetex.py version {1}\n""".format(self.name, version)

```


Don't remove the space before the percent sign above!

L^AT_EX environments such as `align` evaluate their arguments twice after doing `\savecounters@`, so if you do `\sage` inside such an environment, it will result in two labels with the same name in the `.sout` file and the user sees a warning when typesetting. So we keep track of the largest label we've seen so that we don't write two labels with the same name.

```
345     self.max_counter_seen = MyDict()
```

Open a `.sout.tmp` file and write all our output to that. Then, when we're done, we move that to `.sout`. The “autogenerated” line is basically the same as the lines that get put at the top of prepared Sage files; we are automatically generating a file with Sage, so it seems reasonable to add it. Add in the version to help debugging version mismatch problems.

```
346     self.souttmp = open(self.filename + '.sagetex.sout.tmp', 'w')
347     self.souttmp.write(autogenstr)
```

In addition to the `.sout` file, the `sagecommandline` also needs a `.scmd` file. As before, we use a `.scmd.tmp` file and rename it later on. We store the position so that `commandline` can tell the `listings` package what lines in the `.scmd` file to pull in.

```
348     self.scmdtmp = open(self.filename + '.sagetex.scmd.tmp', 'w')
349     self.scmdtmp.write(autogenstr)
350     self.scmdpos = 3
```

progress This function just prints stuff. It allows us to not print a linebreak, so you can get “start...” (little time spent processing) “end” on one line.

```
351     def progress(self, t, linebreak=True):
352         if linebreak:
353             print(t)
354         else:
355             sys.stdout.write(t)
356             sys.stdout.flush()
```

initplot We only want to create the plots directory if the user actually plots something. This function creates the directory and sets the `didinitplot` flag after doing so. We make a directory based on the L^AT_EX file being processed so that if there are multiple `.tex` files in a directory, we don't overwrite plots from another file.

```
357     def initplot(self):
358         self.progress('Initializing plots directory')
```

We hard-code the `.tex` extension, which is fine in the overwhelming majority of cases, although it does cause minor confusion when building the documentation. If it turns out lots of people use, say, a `ltx` extension or whatever, We could find out the correct extension, but it would involve a lot of irritating mucking around—on `comp.text.tex`, the best solution I found for finding the file extension is to look through the `.log` file. (Although see the `currfile` package.)

```
359     if os.path.isdir(self.plotdir):
360         shutil.rmtree(self.plotdir)
```

```

361     os.mkdir(self.plotdir)
362     self.didinitplot = True

```

`inline` This function works with `\sage` from the style file (see section 6.1.2) to put Sage output into your \LaTeX file. Usually, when you use `\label`, it writes a line such as

```
\newlabel{labelname}{{section number}{page number}}
```

to the `.aux` file. When you use the `hyperref` package, there are more fields in the second argument, but the first two fields are the same. The `\ref` command just pulls in what's in the first field of the second argument, so we can hijack this mechanism for our own nefarious purposes. The function writes a `\newlabel` line with a label made from a counter and the text from running Sage on `s`.

When the user does `\sage` inside certain displayed math environments (`align` is the most common culprit) this function will get called twice with exactly the same arguments. We check to see what labels we've seen and immediately bail if we've written this label before.

The `labelname` defaults to the the name used by the usual `\sage` inline macro, but this function is also used by the `sagecommandline` environment. It's important to keep the corresponding labels separate, because `\sage` macros often (for example) appear inside math mode, and the labels from `sagecommandline` contain a `lstlistings` environment—pulling such an environment into math mode produces strange, unrecoverable errors, and if you can't typeset your file, you can't produce an updated `.sagetex.sage` file to run Sage on to produce a reasonable `.sagetext.sout` file that will fix the label problem. So it works much better to use distinct labels for such things.

We print out the line number so if something goes wrong, the user can more easily track down the offending `\sage` command in the source file.

That's a lot of explanation for a short function:

```

363 def inline(self, counter, s, labelname='sageinline'):
364     if counter <= self.max_counter_seen[labelname]:
365         return
366     else:
367         self.max_counter_seen.increment(labelname)
368     if labelname == 'sageinline':
369         self.progress('Inline formula {0} (line {1})'.format(counter, self.current_tex_line))
370     elif labelname == 'sagecmdline':
371         pass # output message already printed
372     else:
373         raise ValueError, 'inline() got a bad labelname "{0}"'.format(labelname)
374     self.souttmp.write(r'\newlabel{@' + labelname + str(counter) +
375                       '}' + s.rstrip() + '}' + '\n')

```

We are using five fields, just like `hyperref` does, because that works whether or not `hyperref` is loaded. Using two fields, as in plain \LaTeX , doesn't work if `hyperref` is loaded.

savecmd Analogous to `inline`, this method saves the input string `s` to the `souttmp` file. It returns the first and last line of the newly-added output so that `commandline` can tell the `listings` package where to get stuff.

```

376 def savecmd(self, s):
377     self.scmdtmp.write(s.rstrip() + "\n")
378     begin = self.scmdpos
379     end = begin + len(s.splitlines()) - 1
380     self.scmdpos = end + 1
381     return begin, end

```

blockbegin This function and its companion used to write stuff to the `.sout` file, but now they
blockend just update the user on our progress evaluating a code block. The verbatim-like environments of section 6.1.4 use these functions.

```

382 def blockbegin(self):
383     self.progress('Code block (line {}) begin...'.format(self.current_tex_line), False)
384 def blockend(self):
385     self.progress('end')

```

splitsagecmds Given a string `s` of doctest-like Sage code, this function returns a list of tuples `(i, j, cmd)`, where `cmd` is a string representing a Sage command, with the initial prompt and continuation lines stripped, `i` is the position in `s` where `cmd` starts, and `j` is the starting position in `s` of the purported output from the command that was included in `s`.

This is used by `doctest` and `commandline`, below.
 For example, this turns the string

```

'''
    sage: 1+1
    2
    sage: y = 1729
    sage: 10^3 + 9^3 == 12^3 + 1^3 == y
    sage: gcd(9999999,
    ....: 123456)
    3
    sage: factor(x^2 + 2*x + 1)
    (x + 1)^2
'''

```

into

```

[(0, 18, '1+1'),
 (28, 51, 'y = 1729'),
 (51, 95, '10^3 + 9^3 == 12^3 + 1^3 == y'),
 (95, 144, 'gcd(9999999,\n123456)'),
 (154, 190, 'factor(x^2 + 2*x + 1)')]

```

You can reconstruct the sequence of commands and their output with something like

```

splitup = split_sage_cmds(s)
oldout = splitup[0][1]
print '=' * 50
print '==== Command:'
print s[splitup[0][0]:oldout]
for start, out, _ in splitup[1:]:
    print '==== Given output:'
    print s[oldout:start]
    print '=' * 50
    print '==== Command:'
    print s[start:out]
    oldout = out
print '==== Given output:'
print s[oldout:]

386 def split_sage_cmds(self, s):
387     prompt = '\n' + r'\s*sage: '
388     cont = r'\s*\.\.\.\.: '

```

Prepending a newline to `s` ensures that the list from `re.split()` begins with something we can ignore—and so that the `re.split()` returns $n + 1$ groups for n matches, so therefore `split` and `starts` match up.

```

389     split = re.split(prompt, '\n' + s)[1:]
390     starts = [m.start() - 1 for m in re.finditer(prompt, '\n' + s)]

```

The prepended newline messes up the first element of `starts`, fix that:

```

391     starts[0] = re.search(prompt, s).start()

```

Now find where the outputs start. We need this because `doctest()` may or may not print the outputs. The idea is: for each `starting` position, advance over the prompt that we know is there, then look for the rightmost continuation marker between the current prompt and the next one, and *then* look for the newline following that. That position is where the output begins.

```

392     outputs = []
393     for i, j in zip(starts, starts[1:] + [len(s)]):
394         k = i + re.match(prompt, s[i:j]).end()
395         try:
396             k += [m.end() for m in re.finditer(cont, s[k:j])][-1]
397         except IndexError:
398             pass
399         end = s.find('\n', k)
400         outputs.append(end)

```

Now we take each command group, split it up, and look for all the continuation lines. We append those, stripping off the continuation marks.

```

401     ret = []
402     for start, end, g in zip(starts, outputs, split):
403         lines = g.splitlines()
404         cmd = lines[:1]
405         for line in lines[1:]:

```

```

406             m = re.match(cont, line)
407             if m:
408                 cmd.append(line[m.end():])
409             ret.append((start, end, '\n'.join(cmd)))
410         return ret

```

doctest This function handles the `sageexample` environment, which typesets Sage code and its output. We call it `doctest` because the format is just like that for doctests in the Sage library.

The idea is:

1. Get the literal text for each command, wrap that in `SaveVerbatim`, write that (possibly with its associated output from the `.tex` file) to the `sout` file.
2. Accumulate a corresponding `UseVerbatim` and typeset output so that we can call `inline()` at the end and pull in all this stuff.
3. For the output: try to `eval()` the processed command (the one with the prompts and continuation marks stripped). If that succeeds, we run `latex()` on it and display that below the verbatim text from above. If that fails, it's because you have a statement and not an expression—there's no output from such a thing (well, none that we can capture, anyway) so no need to typeset output.

```

411 def doctest(self, counter, s, globals, locals, include_text_output):
412     self.progress('Sage example {0} (line {1})'.format(counter, self.current_tex_line))
413     splitup = self.split_sage_cmds(s)
414     tex_strs = []
415     for i in range(len(splitup)):
416         boxname = '@sageinline{}-code{}'.format(counter, i)
417         to_tmp = [r'\begin{SaveVerbatim}{' + boxname + '}',
418                 s[splitup[i][0]:splitup[i][1]]]
419         if include_text_output:
420             try:
421                 to_tmp.append(s[splitup[i][1]:splitup[i+1][0]])
422             except IndexError:
423                 to_tmp.append(s[splitup[i][1]:])
424         to_tmp.append(r'\end{SaveVerbatim}\n')
425         self.souttmp.write(joinone('\n', to_tmp))

```

Now we build up something that we can send to `inline()`, which will pull it into the document using its usual label mechanism.

The verbatim stuff seems to end with a bit of vertical space, so don't start the `displaymath` environment with unnecessary vertical space—the `displayskip` stuff is from §11.5 of Herbert Voß's "Math Mode".

```

426         tex_strs.append(r'\UseVerbatim{' + boxname + '}')
427         try:
428             result = eval(preparse(splitup[i][2]), globals, locals)
429             tex_strs += [r'\abovedisplayskip=0pt plus 3pt ',
430                        r'\abovedisplayshortskip=0pt plus 3pt ',

```

```

431             r'\begin{displaymath}',
432             latex(result),
433             r' \end{displaymath}']
434         except SyntaxError:
435             exec preparse(splitup[i][2]) in globals, locals
436         self.inline(counter, '\n'.join(tex_strs))

```

`commandline` This function handles the `commandline` environment, which typesets Sage code, computes its output, and typesets that too. This is very similar to `doctest` and I hope to someday combine them into one.

Even if I can't refactor these two functions (and their associated environments) into one, I would like to eliminate the `.scmd` file that this function uses, since exactly the same bits of Sage code get written to both the `.scmd` file and the `_doctest.sage` file. The reason this isn't trivial is because we need to keep track of which line number we're on so that we can give the `listings` package a start and end line to extract, and right now the `_doctest.sage` file is written to by L^AT_EX and we can't track the line number.

In any case, here's what we do: after splitting up the provided string using `split_sage_cmds`, we iterate over each of the commands and:

1. Put the original input command into the `.scmd` file with `savecmd`.
2. Use the `begin` and `end` line numbers to append a `lstinputlisting` command to the T_EX commands we'll eventually hand off to `inline`.
3. Evaluate the command using `eval()` or `exec`, as necessary. If we're doing plain text format, we send the output to the `.scmd` file and add a T_EX command to pull that back in—if we need typeset output, then we just hit the output with `latex()` and add that to the list of T_EX commands.

Observe that we detect spaces in the filename and quote that for T_EX if we need to.

```

437 def commandline(self, counter, s, globals, locals, text_output):
438     self.progress('Sage commandline {0} (line {1})'.format(counter, self.current_tex_line))
439     scmd_fn = self.name + '.sagetex.scmd'
440     if ' ' in scmd_fn:
441         scmd_fn = '"{}"'.format(scmd_fn)
442
443     splitup = self.split_sage_cmds(s)
444     skip = r'\vspace{\sagecommandlineskip}'
445     tex_strs = [skip]
446     lstinput = r'\lstinputlisting[firstline={0},lastline={1},firstnumber={2},style=SageInput{
447     for i in range(len(splitup)):
448         orig_input = s[splitup[i][0]:splitup[i][1]]
449         begin, end = self.savecmd(strip_common_leading_spaces(orig_input.strip('\n')))
450         if '#@' in orig_input:
451             escapeoption = ',escapeinside={\\#@}{\\^M}'
452         else:
453             escapeoption = ''

```

```

454         tex_strs.append(lstinput.format(begin, end, begin - 2, scmd_fn, escape=escapeoption))
455     try:
456         result = eval(preparse(splitup[i][2]), globals, locals)
457         if text_output:
458             begin, end = self.savecmd(str(result))
459             tex_strs.append(lstinput.format(begin, end, begin - 2, scmd_fn, escape=''))
460         else:
461             tex_strs.append(r'\begin{displaymath}' +
462                             latex(result) +
463                             r'\end{displaymath}')
464     except SyntaxError:
465         exec preparse(splitup[i][2]) in globals, locals
466     if 'displaymath' not in tex_strs[-1]:
467         tex_strs.append(skip)
468     self.inline(counter, '\n'.join(tex_strs), labelname='sagecmdline')

```

`plot` I hope it's obvious that this function does plotting. It's the Python counterpart of `\ST@sageplot` described in section 6.1.3. As mentioned in the `\sageplot` code, we're taking advantage of two things: first, that \LaTeX doesn't treat commas and spaces in macro arguments specially, and second, that Python (and Sage plotting functions) has nice support for keyword arguments. The `#3` argument to `\sageplot` becomes `_p_` and `**kwargs` below.

```

469 def plot(self, counter, _p_, format='notprovided', **kwargs):
470     if not self.didinitplot:
471         self.initplot()
472     self.progress('Plot {0} (line {1})'.format(counter, self.current_tex_line))

```

If the user says nothing about file formats, we default to producing PDF and EPS. This allows the user to transparently switch between using a DVI previewer (which usually automatically updates when the DVI changes, and has support for source specials, which makes the writing process easier) and making PDFs.⁵

```

473     if format == 'notprovided':
474         formats = ['eps', 'pdf']
475     else:
476         formats = [format]
477     for fmt in formats:

```

If we're making a PDF and have been told to use `epstopdf`, do so, then skip the rest of the loop.

```

478         if fmt == 'pdf' and self.useepstopdf:
479             epsfile = os.path.join(self.plotdir, 'plot-{0}.eps'.format(counter))
480             self.progress('Calling epstopdf to convert plot-{0}.eps to PDF'.format(
481                 counter))
482             subprocess.check_call(['epstopdf', epsfile])
483             continue

```

Some plot objects (mostly 3-D plots) do not support saving to EPS or PDF files (yet), but everything can be saved to a PNG file. For the user's convenience, we

⁵Yes, there's `pdfsync`, but full support for that is still rare in Linux, so producing EPS and PDF is the best solution for now.

catch the error when we run into such an object, save it to a PNG file, then exit the loop.

```

484         plotfilename = os.path.join(self.plotdir, 'plot-{0}.{1}'.format(counter, fmt))
485         try:
486             _p_.save(filename=plotfilename, **kwargs)
487         except ValueError as inst:
488             if re.match('filetype .*not supported by save', str(inst)):
489                 newfilename = plotfilename[:-3] + 'png'
490                 print ' saving {0} failed; saving to {1} instead.'.format(
491                     plotfilename, newfilename)
492                 _p_.save(filename=newfilename, **kwargs)
493                 break
494             else:
495                 raise

```

If the user provides a format *and* specifies the `imagemagick` option, we try to convert the newly-created file into EPS format.

```

496         if format != 'notprovided' and self.useimagemagick:
497             self.progress('Calling Imagemagick to convert plot-{0}.{1} to EPS'.format(
498                 counter, format))
499             self.toeps(counter, format)

```

toeps This function calls the `Imagemagick` utility `convert` to, well, convert something into EPS format. This gets called when the user has requested the “`imagemagick`” option to the `SageTeX` style file and is making a graphic file with a nondefault extension.

```

500     def toeps(self, counter, ext):
501         subprocess.check_call(['convert', \
502             '{0}/plot-{1}.{2}'.format(self.plotdir, counter, ext), \
503             '{0}/plot-{1}.eps'.format(self.plotdir, counter)])

```

We are blindly assuming that the `convert` command exists and will do the conversion for us; the `check_call` function raises an exception which, since all these calls get wrapped in `try/excepts` in the `.sage` file, should result in a reasonable error message if something strange happens.

goboom When a chunk of Sage code blows up, this function bears the bad news to the user. Normally in Python the traceback is good enough for this, but in this case, we start with a `.sage` file (which is autogenerated) which itself autogenerates a `.py` file—and the tracebacks the user sees refer to that file, whose line numbers are basically useless. We want to tell them where in the `LATEX` file things went bad, so we do that, give them the traceback, and exit after removing the `.sout.tmp` and `.scmd.tmp` file.

```

504     def goboom(self, line):
505         print('\n**** Error in Sage code on line {0} of {1}.tex! Traceback\
506 follows.'.format(line, self.filename))
507         traceback.print_exc()
508         print('\n**** Running Sage on {0}.sage failed! Fix {0}.tex and try\
509 again.'.format(self.filename))

```



```

510     self.souttmp.close()
511     os.remove(self.filename + '.sagetex.sout.tmp')
512     self.scmdtmp.close()
513     os.remove(self.filename + '.sagetex.scmd.tmp')
514     sys.exit(int(1))

```

We use `int(1)` above to make sure `sys.exit` sees a Python integer; see ticket #2861.

`endofdoc` When we're done processing, we have some cleanup tasks. We want to put the MD5 sum of the `.sage` file that produced the `.sout` file we're about to write into the `.sout` file, so that external programs that build L^AT_EX documents can determine if they need to call Sage to update the `.sout` file. But there is a problem: we write line numbers to the `.sage` file so that we can provide useful error messages—but that means that adding non-SageT_EX text to your source file will change the MD5 sum, and your program will think it needs to rerun Sage even though none of the actual SageT_EX macros changed.

How do we include line numbers for our error messages but still allow a program to discover a “genuine” change to the `.sage` file?

The answer is to only find the MD5 sum of *part* of the `.sage` file. By design, the source file line numbers only appear in (1) calls to `goboom`, (2) lines with `_st.current_tex_line`, and (3) pause/unpause lines, so we will strip those lines out. What we do below is exactly equivalent to running

```
egrep -v '^( _st.goboom| ?_st.current_tex_line|print .SageT)' filename.sage | md5sum
```

in a shell. The included `run-sagetex-if-necessary` uses this mechanism to, well, only run Sage when necessary; see section 7.1.

```

515     def endofdoc(self):
516         sagef = open(self.filename + '.sagetex.sage', 'r')
517         m = hashlib.md5()
518         for line in sagef:
519             if not line.startswith((" _st.goboom",
520                                     "print 'SageT",
521                                     "_st.current_tex_line",
522                                     " _st.current_tex_line")):
523                 m.update(line)

```

(The `current_tex_line` thing appears twice because it may appear indented one space or not, depending on whether it's used before `blockbegin` or not.)

```

524         s = '%' + m.hexdigest() + '% md5sum of corresponding .sage file\
525 (minus "goboom", "current_tex_line", and pause/unpause lines)\n'
526         self.souttmp.write(s)
527         self.scmdtmp.write(s)

```

Now, we do issue warnings to run Sage on the `.sage` file and an external program might look for those to detect the need to rerun Sage, but those warnings do not quite capture all situations. (If you've already produced the `.sout` file and change a `\sage` call, no warning will be issued since all the `\refs` find a

\newlabel.) Anyway, I think it's easier to grab an MD5 sum out of the end of the file than parse the output from running `latex` on your file. (The regular expression `^[0-9a-f]{32}%` will find the MD5 sum. Note that there are percent signs on each side of the hex string.)

Now we are done with the `.sout.tmp` file. Close it, rename it, and tell the user we're done.

```
528     self.souttmp.close()
529     os.rename(self.filename + '.sagetex.sout.tmp', self.filename + '.sagetex.sout')
530     self.scmdtmp.close()
531     os.rename(self.filename + '.sagetex.scmd.tmp', self.filename + '.sagetex.scmd')
532     self.progress('Sage processing complete. Run LaTeX on {0}.tex again.'.format(
533         self.filename))
```

7 Included Python scripts

Here we describe the Python code for `run-sagetex-if-necessary`, and also `makestatic.py`, which removes SageTeX commands to produce a “static” file, and `extractsagecode.py`, which extracts all the Sage code from a `.tex` file.

7.1 run-sagetex-if-necessary

When working on a document that uses SageTeX, running Sage every time you typeset your document may take too long, especially since it often won't be necessary. This script is a drop-in replacement for Sage: instead of

```
sage document.sagetex.sage
```

you can do

```
run-sagetex-if-necessary.py document.sagetex.sage
```

and it will use the MD5 mechanism described in the `endofdoc` macro (page 41). With this, you can set up your editor (TeXShop, TeXWorks, etc) to typeset your document with a script that does

```
pdflatex $1
run-sagetex-if-necessary.py $1
```

which will only, of course, run Sage when necessary.

```
534
535 # given a filename f, examines f.sagetex.sage and f.sagetex.sout and
536 # runs Sage if necessary.
537
538 import hashlib
539 import sys
540 import os
541 import re
542 import subprocess
```

```

543
544 # CHANGE THIS AS APPROPRIATE
545 path_to_sage = os.path.expanduser('~/.bin/sage')
546 # or try to auto-find it:
547 # path_to_sage = subprocess.check_output(['which', 'sage']).strip()
548 # or just tell me:
549 # path_to_sage = '/usr/local/bin/sage'
550
551 if sys.argv[1].endswith('.sagetex.sage'):
552     src = sys.argv[1][:-13]
553 else:
554     src = os.path.splitext(sys.argv[1])[0]
555
556 commented_out = r'^\s*%'
557 usepackage = r'\usepackage{sagetex}'
558 uses_sagetex = False
559
560 # if it doesn't use sagetex, obviously running sage is unnecessary
561 with open(src + '.tex') as texf:
562     for line in texf:
563         if not re.search(commented_out, line) and re.search(usepackage, line):
564             uses_sagetex = True
565             break
566
567 if not uses_sagetex:
568     print src + ".tex doesn't seem to use SageTeX, exiting."
569     sys.exit(0)
570
571 # if something goes wrong, assume we need to run Sage
572 run_sage = True
573 ignore = r"^( _st_.goboom|print 'SageT| ?_st_.current_tex_line)"
574
575 try:
576     with open(src + '.sagetex.sage', 'r') as sagef:
577         h = hashlib.md5()
578         for line in sagef:
579             if not re.search(ignore, line):
580                 h.update(line)
581 except IOError:
582     print '{0}.sagetex.sage not found, I think you need to typeset {0}.tex first.'.format(src)
583     sys.exit(1)
584
585 try:
586     with open(src + '.sagetex.sout', 'r') as outf:
587         for line in outf:
588             m = re.match('%([0-9a-f]+)% md5sum', line)
589             if m:
590                 print 'computed md5:', h.hexdigest()
591                 print 'sagetex.sout md5:', m.group(1)
592                 if h.hexdigest() == m.group(1):

```

```

593             run_sage = False
594             break
595 except IOError:
596     pass
597
598 if run_sage:
599     print 'Need to run Sage on {0}.'.format(src)
600     sys.exit(subprocess.call([path_to_sage, src + '.sagetex.sage']))
601 else:
602     print 'Not necessary to run Sage on {0}.'.format(src)

```

7.2 makestatic.py

Now the `makestatic.py` script. It's about the most basic, generic Python script taking command-line arguments that you'll find. The `#!/usr/bin/env python` line is provided for us by the `.ins` file's preamble, so we don't put it here.

```

603 import sys
604 import time
605 import getopt
606 import os.path
607 from sagetexparse import DeSageTex
608
609 def usage():
610     print("""Usage: %s [-h|--help] [-o|--overwrite] inputfile [outputfile]
611
612 Removes SageTeX macros from 'inputfile' and replaces them with the
613 Sage-computed results to make a "static" file. You'll need to have run
614 Sage on 'inputfile' already.
615
616 'inputfile' can include the .tex extension or not. If you provide
617 'outputfile', the results will be written to a file of that name.
618 Specify '-o' or '--overwrite' to overwrite the file if it exists.
619
620 See the SageTeX documentation for more details.""" % sys.argv[0])
621
622 try:
623     opts, args = getopt.getopt(sys.argv[1:], 'ho', ['help', 'overwrite'])
624 except getopt.GetoptError, err:
625     print str(err)
626     usage()
627     sys.exit(2)
628
629 overwrite = False
630 for o, a in opts:
631     if o in ('-h', '--help'):
632         usage()
633         sys.exit()
634     elif o in ('-o', '--overwrite'):
635         overwrite = True

```

```

636
637 if len(args) == 0 or len(args) > 2:
638     print('Error: wrong number of arguments. Make sure to specify options first.\n')
639     usage()
640     sys.exit(2)
641
642 if len(args) == 2 and (os.path.exists(args[1]) and not overwrite):
643     print('Error: %s exists and overwrite option not specified.' % args[1])
644     sys.exit(1)
645
646 src, ext = os.path.splitext(args[0])

```

All the real work gets done in the line below. Sorry it's not more exciting-looking.

```

647 desagetexed = DeSageTex(src)

```

This part is cool: we need double percent signs at the beginning of the line because Python needs them (so they get turned into single percent signs) *and* because Docstrip needs them (so the line gets passed into the generated file). It's perfect!

```

648 header = "%% SageTeX commands have been automatically removed from this file and\n%% replaced w
649
650 if len(args) == 2:
651     dest = open(args[1], 'w')
652 else:
653     dest = sys.stdout
654
655 dest.write(header)
656 dest.write(desagetexed.result)

```

7.3 extractsagecode.py

Same idea as makestatic.py, except this does basically the opposite thing.

```

657 import sys
658 import time
659 import getopt
660 import os.path
661 from sagetexparse import SageCodeExtractor
662
663 def usage():
664     print("""Usage: %s [-h|--help] [-o|--overwrite] inputfile [outputfile]
665
666 Extracts Sage code from 'inputfile'.
667
668 'inputfile' can include the .tex extension or not. If you provide
669 'outputfile', the results will be written to a file of that name,
670 otherwise the result will be printed to stdout.
671
672 Specify '-o' or '--overwrite' to overwrite the file if it exists.
673
674 See the SageTeX documentation for more details.""")
675
675

```

```

676 try:
677     opts, args = getopt.getopt(sys.argv[1:], 'ho', ['help', 'overwrite'])
678 except getopt.GetoptError, err:
679     print str(err)
680     usage()
681     sys.exit(2)
682
683 overwrite = False
684 for o, a in opts:
685     if o in ('-h', '--help'):
686         usage()
687         sys.exit()
688     elif o in ('-o', '--overwrite'):
689         overwrite = True
690
691 if len(args) == 0 or len(args) > 2:
692     print('Error: wrong number of arguments. Make sure to specify options first.\n')
693     usage()
694     sys.exit(2)
695
696 if len(args) == 2 and (os.path.exists(args[1]) and not overwrite):
697     print('Error: %s exists and overwrite option not specified.' % args[1])
698     sys.exit(1)
699
700 src, ext = os.path.splitext(args[0])
701 sagecode = SageCodeExtractor(src)
702 header = """\
703 # This file contains Sage code extracted from %s%s.
704 # Processed %s.
705
706 """ % (src, ext, time.strftime('%a %d %b %Y %H:%M:%S', time.localtime()))
707
708 if len(args) == 2:
709     dest = open(args[1], 'w')
710 else:
711     dest = sys.stdout
712
713 dest.write(header)
714 dest.write(sagecode.result)

```

7.4 The parser module

Here's the module that does the actual parsing and replacing. It's really quite simple, thanks to the awesome Pyparsing module. The parsing code below is nearly self-documenting! Compare that to fancy regular expressions, which sometimes look like someone sneezed punctuation all over the screen.

```

715 import sys
716 from pyparsing import *

```

First, we define this very helpful parser: it finds the matching bracket, and doesn't

parse any of the intervening text. It's basically like hitting the percent sign in Vim. This is useful for parsing L^AT_EX stuff, when you want to just grab everything enclosed by matching brackets.

```

717 def skipToMatching(opener, closer):
718     nest = nestedExpr(opener, closer)
719     nest.setParseAction(lambda l, s, t: l[s:getTokensEndLoc()])
720     return nest
721
722 curlybrackets = skipToMatching('{', '}')
723 squarebrackets = skipToMatching('[', ']')

```

Next, parser for `\sage`, `\sageplot`, and `pause/unpause` calls:

```

724 sagemacroparser = r'\sage' + curlybrackets('code')
725 sageplotparser = (r'\sageplot'
726                   + Optional(squarebrackets)('opts')
727                   + Optional(squarebrackets)('format')
728                   + curlybrackets('code'))
729 sagetexpause = Literal(r'\sagetexpause')
730 sagetexunpause = Literal(r'\sagetexunpause')

```

With those defined, let's move on to our classes.

SoutParser Here's the parser for the generated `.sout` file. The code below does all the parsing of the `.sout` file and puts the results into a list. Notice that it's on the order of 10 lines of code—hooray for Pyparsing!

```

731 class SoutParser():
732     def __init__(self, fn):
733         self.label = []

```

A label line looks like

```
\newlabel{@sageinline<integer>}{\{<bunch of LATEX code>\}\}\}\}
```

which makes the parser definition below pretty obvious. We assign some names to the interesting bits so the `newlabel` method can make the `<integer>` and `<bunch of LATEX code>` into the keys and values of a dictionary. The `DeSageTeX` class then uses that dictionary to replace bits in the `.tex` file with their Sage-computed results.

```

734     parselabel = (r'\newlabel{@sageinline'
735                  + Word(nums)('num')
736                  + '}\{'
737                  + curlybrackets('result')
738                  + '\}\}\}\}\}')

```

We tell it to ignore comments, and hook up the list-making method.

```

739     parselabel.ignore('%' + restOfLine)
740     parselabel.setParseAction(self.newlabel)

```

A `.sout` file consists of one or more such lines. Now go parse the file we were given.

```

741     try:

```

```

742     OneOrMore(parselabel).parseFile(fn)
743 except IOError:
744     print 'Error accessing %s; exiting. Does your .sout file exist?' % fn
745     sys.exit(1)

```

Pyparser's parse actions get called with three arguments: the string that matched, the location of the beginning, and the resulting parse object. Here we just add a new key-value pair to the dictionary, remembering to strip off the enclosing brackets from the "result" bit.

```

746 def newlabel(self, s, l, t):
747     self.label.append(t.result[1:-1])

```

DeSageTeX Now we define a parser for L^AT_EX files that use SageT_EX commands. We assume that the provided fn is just a basename.

```

748 class DeSageTex():
749     def __init__(self, fn):
750         self.sagen = 0
751         self.plotn = 0
752         self.fn = fn
753         self.sout = SoutParser(fn + '.sagetex.sout')

```

Parse \sage macros. We just need to pull in the result from the .sout file and increment the counter—that's what self.sage does.

```

754     smacro = sagemacroparser
755     smacro.setParseAction(self.sage)

```

Parse the \usepackage{sagetex} line. Right now we don't support comma-separated lists of packages.

```

756     usepackage = (r'\usepackage'
757                   + Optional(squarebrackets)
758                   + '{sagetex}')
759     usepackage.setParseAction(replaceWith(r'"" "% \usepackage{sagetex}" line was here:
760 \RequirePackage{verbatim}
761 \RequirePackage{graphicx}
762 \newcommand{\sagetexpause}{\relax}
763 \newcommand{\sagetexunpause}{\relax}""'))

```

Parse \sageplot macros.

```

764     splot = sageplotparser
765     splot.setParseAction(self.plot)

```

The printed environments (sageblock and sageverbatim) get turned into verbatim environments.

```

766     beginorend = oneOf('begin end')
767     blockorverb = 'sage' + oneOf('block verbatim')
768     blockorverb.setParseAction(replaceWith('verbatim'))
769     senv = '\\ ' + beginorend + '{' + blockorverb + '}'

```

The non-printed sagesilent environment gets commented out. We could remove all the text, but this works and makes going back to SageT_EX commands (de-de-SageT_EXing?) easier.


```

770     silent = Literal('sagesilent')
771     silent.setParseAction(replaceWith('comment'))
772     ssilent = '\\\\' + beginorend + '{' + silent + '}'

```

The `\sagetexindent` macro is no longer relevant, so remove it from the output (“suppress”, in Pyparsing terms).

```

773     stexindent = Suppress(r'\setlength{\sagetexindent}' + curlybrackets)

```

Now we define the parser that actually goes through the file. It just looks for any one of the above bits, while ignoring anything that should be ignored.

```

774     doit = smacro | senv | ssilent | usepackage | splot | stexindent
775     doit.ignore('%' + restOfLine)
776     doit.ignore(r'\begin{verbatim}' + SkipTo(r'\end{verbatim}'))
777     doit.ignore(r'\begin{comment}' + SkipTo(r'\end{comment}'))
778     doit.ignore(r'\sagetexpause' + SkipTo(r'\sagetexunpause'))

```

We can’t use the `parseFile` method, because that expects a “complete grammar” in which everything falls into some piece of the parser. Instead we suck in the whole file as a single string, and run `transformString` on it, since that will just pick out the interesting bits and munge them according to the above definitions.

```

779     str = ''.join(open(fn + '.tex', 'r').readlines())
780     self.result = doit.transformString(str)

```

That’s the end of the class constructor, and it’s all we need to do here. You access the results of parsing via the `result` string.

We do have two methods to define. The first does the same thing that `\ref` does in your \LaTeX file: returns the content of the label and increments a counter.

```

781     def sage(self, s, l, t):
782         self.sagen += 1
783         return self.sout.label[self.sagen - 1]

```

The second method returns the appropriate `\includegraphics` command. It does need to account for the default argument.

```

784     def plot(self, s, l, t):
785         self.plotn += 1
786         if len(t.opts) == 0:
787             opts = r'[width=.75\textwidth]'
788         else:
789             opts = t.opts[0]
790         return (r'\includegraphics{s{sage-plots-for-%s.tex/plot-%s}}' %
791             (opts, self.fn, self.plotn - 1))

```

SageCodeExtractor This class does the opposite of the first: instead of removing Sage stuff and leaving only \LaTeX , this removes all the \LaTeX and leaves only Sage.

```

792 class SageCodeExtractor():
793     def __init__(self, fn):
794         smacro = sagemacroparser
795         smacro.setParseAction(self.macroout)
796
797         splot = sageplotparser
798         splot.setParseAction(self.plotout)

```

Above, we used the general parsers for `\sage` and `\sageplot`. We have to redo the environment parsers because it seems too hard to define one parser object that will do both things we want: above, we just wanted to change the environment name, and here we want to suck out the code. Here, it's important that we find matching begin/end pairs; above it wasn't. At any rate, it's not a big deal to redo this parser.

```

799     env_names = oneOf('sageblock sageverbatim sagesilent')
800     senv = r'\begin{' + env_names('env') + '}' + SkipTo(
801         r'\end{' + matchPreviousExpr(env_names) + '}')('code')
802     senv.leaveWhitespace()
803     senv.setParseAction(self.envout)
804
805     spause = sagetexpause
806     spause.setParseAction(self.pause)
807
808     sunpause = sagetexunpause
809     sunpause.setParseAction(self.unpause)
810
811     doit = smacro | splot | senv | spause | sunpause
812
813     str = ''.join(open(fn + '.tex', 'r').readlines())
814     self.result = ''
815
816     doit.transformString(str)
817
818     def macroout(self, s, l, t):
819         self.result += '# \\sage{} from line %s\n' % lineno(l, s)
820         self.result += t.code[1:-1] + '\n\n'
821
822     def plotout(self, s, l, t):
823         self.result += '# \\sageplot{} from line %s\n' % lineno(l, s)
824         if t.format is not '':
825             self.result += '# format: %s' % t.format[0][1:-1] + '\n'
826         self.result += t.code[1:-1] + '\n\n'
827
828     def envout(self, s, l, t):
829         self.result += '# %s environment from line %s:' % (t.env,
830             lineno(l, s))
831         self.result += t.code[0] + '\n'
832
833     def pause(self, s, l, t):
834         self.result += ('# SageTeX (probably) paused on input line %s.\n\n' %
835             (lineno(l, s)))
836
837     def unpause(self, s, l, t):
838         self.result += ('# SageTeX (probably) unpaused on input line %s.\n\n' %
839             (lineno(l, s)))

```

8 The remote-sagetex script

Here we describe the Python code for `remote-sagetex.py`. Since its job is to replicate the functionality of using Sage and `sagetex.py`, there is some overlap with the Python module.

The `#!/usr/bin/env python` line is provided for us by the `.ins` file's preamble, so we don't put it here.

```
840 from __future__ import print_function
841 import json
842 import sys
843 import time
844 import re
845 import urllib
846 import hashlib
847 import os
848 import os.path
849 import shutil
850 import getopt
851 from contextlib import closing
852
853 #####
854 # You can provide a filename here and the script will read your login #
855 # information from that file. The format must be:                      #
856 #                                                                    #
857 # server = 'http://foo.com:8000'                                       #
858 # username = 'my_name'                                                #
859 # password = 's33krit'                                                #
860 #                                                                    #
861 # You can omit one or more of those lines, use " quotes, and put hash #
862 # marks at the beginning of a line for comments. Command-line args   #
863 # take precedence over information from the file.                      #
864 #####
865 login_info_file = None          # e.g. '/home/foo/Private/sagetex-login.txt'
866
867
868 usage = """Process a SageTeX-generated .sage file using a remote Sage server.
869
870 Usage: {0} [options] inputfile.sage
871
872 Options:
873
874     -h, --help:          print this message
875     -s, --server:        the Sage server to contact
876     -u, --username:      username on the server
877     -p, --password:      your password
878     -f, --file:          get login information from a file
879
880 If the server does not begin with the four characters 'http', then
881 'https://' will be prepended to the server name.
```

```

882
883 You can hard-code the filename from which to read login information into
884 the remote-sagetex script. Command-line arguments take precedence over
885 the contents of that file. See the SageTeX documentation for formatting
886 details.
887
888 If any of the server, username, and password are omitted, you will be
889 asked to provide them.
890
891 See the SageTeX documentation for more details on usage and limitations
892 of remote-sagetex. """ .format(sys.argv[0])
893
894 server, username, password = (None,) * 3
895
896 try:
897     opts, args = getopt.getopt(sys.argv[1:], 'hs:u:p:f:',
898                                ['help', 'server=', 'user=', 'password=', 'file='])
899 except getopt.GetoptError as err:
900     print(str(err), usage, sep='\n\n')
901     sys.exit(2)
902
903 for o, a in opts:
904     if o in ('-h', '--help'):
905         print(usage)
906         sys.exit()
907     elif o in ('-s', '--server'):
908         server = a
909     elif o in ('-u', '--user'):
910         username = a
911     elif o in ('-p', '--password'):
912         password = a
913     elif o in ('-f', '--file'):
914         login_info_file = a
915
916 if len(args) != 1:
917     print('Error: must specify exactly one file. Please specify options first.',
918           usage, sep='\n\n')
919     sys.exit(2)
920
921 jobname = os.path.splitext(args[0])[0]

```

When we send things to the server, we get everything back as a string, including tracebacks. We can search through output using regexps to look for typical traceback strings, but there's a more robust way: put in a special string that changes every time and is printed when there's an error, and look for that. Then it is massively unlikely that a user's code could produce output that we'll mistake for an actual traceback. System time will work well enough for these purposes. We produce this string now, and use it when parsing the `.sage` file (we insert it into code blocks) and when parsing the output that the remote server gives us.

```

922 traceback_str = 'Exception in SageTeX session {0}:'.format(time.time())

```

`parsedotsage` To figure out what commands to send the remote server, we actually read in the `.sage` file as strings and parse it. This seems a bit strange, but since we know exactly what the format of that file is, we can parse it with a couple flags and a handful of regexps.

```
923 def parsedotsage(fn):
924     with open(fn, 'r') as f:

Here are the regexps we use to snarf the interesting bits out of the .sage file.
Below we'll use the re module's match function so we needn't anchor any of these
at the beginning of the line.

925     inline = re.compile(r"_st_.inline\((?P<num>\d+), (?P<code>.*)\)")
926     plot = re.compile(r"_st_.plot\((?P<num>\d+), (?P<code>.*)\)")
927     goboom = re.compile(r"_st_.goboom\((?P<num>\d+)\)")
928     pausemsg = re.compile(r"print.'(?P<msg>SageTeX (un)?paused.*)'")
929     blockbegin = re.compile(r"_st_.blockbegin\(\)")
930     ignore = re.compile(r"(try:)|(except):")
931     in_comment = False
932     in_block = False
933     cmds = []
```

Okay, let's go through the file. We're going to make a list of dictionaries. Each dictionary corresponds to something we have to do with the remote server, except for the pause/unpause ones, which we only use to print out information for the user. All the dictionaries have a `type` key, which obviously tells you type they are. The pause/unpause dictionaries then just have a `msg` which we toss out to the user. The "real" dictionaries all have the following keys:

- `type`: one of `inline`, `plot`, and `block`.
- `goboom`: used to help the user pinpoint errors, just like the `goboom` function (page 40) does.
- `code`: the code to be executed.

Additionally, the `inline` and `plot` dicts have a `num` key for the label we write to the `.sout` file.

Here's the whole parser loop. The interesting bits are for parsing blocks because there we need to accumulate several lines of code.

```
934     for line in f.readlines():
935         if line.startswith('"""'):
936             in_comment = not in_comment
937         elif not in_comment:
938             m = pausemsg.match(line)
939             if m:
940                 cmds.append({'type': 'pause',
941                             'msg': m.group('msg')})
942             m = inline.match(line)
943             if m:
944                 cmds.append({'type': 'inline',
945                             'num': m.group('num'),
```

```

946             'code': m.group('code'))}
947     m = plot.match(line)
948     if m:
949         cmds.append({'type': 'plot',
950                     'num': m.group('num'),
951                     'code': m.group('code')})

```

The order of the next three “if”s is important, since we need the “goboom” line and the “blockbegin” line to *not* get included into the block’s code. Note that the lines in the `.sage` file already have some indentation, which we’ll use when sending the block to the server—we wrap the text in a try/except.

```

952         m = goboom.match(line)
953         if m:
954             cmds[-1]['goboom'] = m.group('num')
955             if in_block:
956                 in_block = False
957             if in_block and not ignore.match(line):
958                 cmds[-1]['code'] += line
959             if blockbegin.match(line):
960                 cmds.append({'type': 'block',
961                             'code': ''})
962             in_block = True
963     return cmds

```

Parsing the `.sage` file is simple enough so that we can write one function and just do it. Interacting with the remote server is a bit more complicated, and requires us to carry some state, so let’s make a class.

RemoteSage This is pretty simple; it’s more or less a translation of the examples in `sage/server/simple/twist.py`.

```

964 debug = False
965 class RemoteSage:
966     def __init__(self, server, user, password):
967         self._srv = server.rstrip('/')
968         sep = '___S_A_G_E___'
969         self._response = re.compile('(P<header>.*)' + sep +
970                                     '\n*(P<output>.*)', re.DOTALL)
971         self._404 = re.compile('404 Not Found')
972         self._session = self._get_url('login',
973                                     urllib.urlencode({'username': user,
974                                                         'password':
975                                                         password}))[ 'session']

```

In the string below, we want to do “partial formatting”: we format in the traceback string now, and want to be able to format in the code later. The double braces get ignored by `format()` now, and are picked up by `format()` when we use this later.

```

976         self._codewrap = """try:
977 {{0}}
978 except:

```

```

979     print('{0}')
980     traceback.print_exc()""".format(traceback_str)
981     self.do_block("""
982     import traceback
983     def __st_plot__(counter, _p_, format='notprovided', **kwargs):
984         if format == 'notprovided':
985             formats = ['eps', 'pdf']
986         else:
987             formats = [format]
988         for fmt in formats:
989             plotfilename = 'plot-%s.%s' % (counter, fmt)
990             _p_.save(filename=plotfilename, **kwargs)"""
991
992     def _encode(self, d):
993         return 'session={0}&'.format(self._session) + urllib.urlencode(d)
994
995     def _get_url(self, action, u):
996         with closing(urllib.urlopen(self._srv + '/simple/' + action +
997                                   '?' + u)) as h:
998             data = self._response.match(h.read())
999             result = json.loads(data.group('header'))
1000             result['output'] = data.group('output').rstrip()
1001         return result
1002
1003     def _get_file(self, fn, cell, ofn=None):
1004         with closing(urllib.urlopen(self._srv + '/simple/' + 'file' + '?' +
1005                                   self._encode({'cell': cell, 'file': fn}))) as h:
1006             myfn = ofn if ofn else fn
1007             data = h.read()
1008             if not self._404.search(data):
1009                 with open(myfn, 'w') as f:
1010                     f.write(data)
1011             else:
1012                 print('Remote server reported {0} could not be found:'.format(
1013                       fn))
1014                 print(data)

```

The code below gets stuffed between a try/except, so make sure it's indented!

```

1015     def _do_cell(self, code):
1016         realcode = self._codewrap.format(code)
1017         result = self._get_url('compute', self._encode({'code': realcode}))
1018         if result['status'] == 'computing':
1019             cell = result['cell_id']
1020             while result['status'] == 'computing':
1021                 sys.stdout.write('working...')
1022                 sys.stdout.flush()
1023                 time.sleep(10)
1024             result = self._get_url('status', self._encode({'cell': cell}))
1025         if debug:
1026             print('cell: <<<', realcode, '>>>', 'result: <<<',

```

```

1027         result['output'], '>>>', sep='\n')
1028     return result
1029
1030     def do_inline(self, code):
1031         return self._do_cell(' print(latex({0}))'.format(code))
1032
1033     def do_block(self, code):
1034         result = self._do_cell(code)
1035         for fn in result['files']:
1036             self._get_file(fn, result['cell_id'])
1037         return result
1038
1039     def do_plot(self, num, code, plotdir):
1040         result = self._do_cell(' __st_plot__({0}, {1})'.format(num, code))
1041         for fn in result['files']:
1042             self._get_file(fn, result['cell_id'], os.path.join(plotdir, fn))
1043     return result

```

When using the simple server API, it's important to log out so the server doesn't accumulate idle sessions that take up lots of memory. We define a `close()` method and use this class with the closing context manager that always calls `close()` on the way out.

```

1044     def close(self):
1045         sys.stdout.write('Logging out of {0}...'.format(server))
1046         sys.stdout.flush()
1047         self._get_url('logout', self._encode({}))
1048         print('done')

```

Next we have a little pile of miscellaneous functions and variables that we want to have at hand while doing our work. Note that we again use the traceback string in the error-finding regular expression.

```

1049 def do_plot_setup(plotdir):
1050     printc('initializing plots directory...')
1051     if os.path.isdir(plotdir):
1052         shutil.rmtree(plotdir)
1053     os.mkdir(plotdir)
1054     return True
1055
1056 did_plot_setup = False
1057 plotdir = 'sage-plots-for-' + jobname + '.tex'
1058
1059 def labelline(n, s):
1060     return r'\newlabel{@sageinline' + str(n) + '}{{' + s + '}}{{{}{}}\n'
1061
1062 def printc(s):
1063     print(s, end='')
1064     sys.stdout.flush()
1065
1066 error = re.compile("(" + traceback_str + ")|(^Syntax Error:)", re.MULTILINE)
1067

```



```

1068 def check_for_error(string, line):
1069     if error.search(string):
1070         print("""
1071 **** Error in Sage code on line {0} of {1}.tex!
1072 {2}
1073 **** Running Sage on {1}.sage failed! Fix {1}.tex and try again.""").format(
1074         line, jobname, string))
1075     sys.exit(1)

    Now let's actually start doing stuff.

1076 print('Processing Sage code for {0}.tex using remote Sage server.'.format(
1077     jobname))
1078
1079 if login_info_file:
1080     with open(login_info_file, 'r') as f:
1081         print('Reading login information from {0}.'.format(login_info_file))
1082         get_val = lambda x: x.split('=')[1].strip().strip('\n')
1083         for line in f:
1084             print(line)
1085             if not line.startswith('#'):
1086                 if line.startswith('server') and not server:
1087                     server = get_val(line)
1088                 if line.startswith('username') and not username:
1089                     username = get_val(line)
1090                 if line.startswith('password') and not password:
1091                     password = get_val(line)
1092
1093 if not server:
1094     server = raw_input('Enter server: ')
1095
1096 if not server.startswith('http'):
1097     server = 'https://' + server
1098
1099 if not username:
1100     username = raw_input('Enter username: ')
1101
1102 if not password:
1103     from getpass import getpass
1104     password = getpass('Please enter password for user {0} on {1}: '.format(
1105         username, server))
1106
1107 printc('Parsing {0}.sage...'.format(jobname))
1108 cmds = parsedotsage(jobname + '.sage')
1109 print('done.')
1110
1111 sout = '% This file was *autogenerated* from the file {0}.sage.\n'.format(
1112     os.path.splitext(jobname)[0])
1113
1114 printc('Logging into {0} and starting session...'.format(server))
1115 with closing(RemoteSage(server, username, password)) as sage:

```

```

1116     print('done.')
1117     for cmd in cmds:
1118         if cmd['type'] == 'inline':
1119             printc('Inline formula {0}...'.format(cmd['num']))
1120             result = sage.do_inline(cmd['code'])
1121             check_for_error(result['output'], cmd['goboom'])
1122             sout += labelline(cmd['num'], result['output'])
1123             print('done.')
1124         if cmd['type'] == 'block':
1125             printc('Code block begin...')
1126             result = sage.do_block(cmd['code'])
1127             check_for_error(result['output'], cmd['goboom'])
1128             print('end.')
1129         if cmd['type'] == 'plot':
1130             printc('Plot {0}...'.format(cmd['num']))
1131             if not did_plot_setup:
1132                 did_plot_setup = do_plot_setup(plotdir)
1133             result = sage.do_plot(cmd['num'], cmd['code'], plotdir)
1134             check_for_error(result['output'], cmd['goboom'])
1135             print('done.')
1136         if cmd['type'] == 'pause':
1137             print(cmd['msg'])
1138         if int(time.time()) % 2280 == 0:
1139             printc('Unscheduled offworld activation; closing iris...')
1140             time.sleep(1)
1141             print('end.')
1142
1143 with open(jobname + '.sage', 'r') as sagef:
1144     h = hashlib.md5()
1145     for line in sagef:
1146         if (not line.startswith('_st_.goboom') and
1147             not line.startswith("print 'SageT'")):
1148             h.update(line)

```

Putting the {1} in the string, just to replace it with %, seems a bit weird, but if I put a single percent sign there, Docstrip won't put that line into the resulting .py file—and if I put two percent signs, it replaces them with \MetaPrefix which is ## when this file is generated. This is a quick and easy workaround.

```

1149     sout += """"{0}% md5sum of corresponding .sage file
1150 {1} (minus "goboom" and pause/unpause lines)
1151 """".format(h.hexdigest(), '%')
1152
1153 printc('Writing .sout file...')
1154 with open(jobname + '.sout', 'w') as soutf:
1155     soutf.write(sout)
1156     print('done.')
1157 print('Sage processing complete. Run LaTeX on {0}.tex again.'.format(jobname))

```

9 Credits and acknowledgments

According to the original README file, this system was originally done by Gonzalo Tornaria and Joe Wetherell. Later Harald Schilly made some improvements and modifications. Many of the examples in the `example.tex` file are from Harald.

Dan Drake rewrote and extended the style file (there is effectively zero original code there), made significant changes to the Python module, put both files into Docstrip format, and wrote all the documentation and extra Python scripts.

Many thanks to Jason Grout for his numerous comments, suggestions, and feedback. Thanks to Nicolas Thiéry for the initial code and contributions to the `sageexample` environment and Volker Braun for the `sagecommandline` environment.

10 Copying and licenses

If you are unnaturally curious about the current state of the `SageTeX` package, you can visit <https://github.com/dandrake/sagetex>. (The old Bitbucket repository is deprecated.)

As for the terms and conditions under which you can copy and modify `SageTeX`:

The *source code* of the `SageTeX` package may be redistributed and/or modified under the terms of the GNU General Public License as published by the Free Software Foundation, either version 2 of the License, or (at your option) any later version. To view a copy of this license, see <http://www.gnu.org/licenses/> or send a letter to the Free Software Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA 02110-1301, USA.

The *documentation* of the `SageTeX` package is licensed under the Creative Commons Attribution-Share Alike 3.0 License. To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/3.0/> or send a letter to Creative Commons, 171 Second Street, Suite 300, San Francisco, California, 94105, USA.

I am not terribly dogmatic about these licenses, so if you would like to do something with `SageTeX` that's not possible under these license conditions, please contact me. I will likely be receptive to suggestions.

Change History

v1.0	General: Add typeout if .sout file not found	22
General: Initial version		1
v1.1	endofdoc : Fix bug in finding md5 sum introduced by pause facility	42
General: Wrapped user-provided Sage code in try/except clauses; plotting now has optional format argument		1
v1.2	General: Imagemagick option; better documentation	1
v1.3	\sageplot : Iron out warnings, cool TikZ flowchart	23
v1.3.1	General: Internal variables renamed; fixed typos	1
v1.4	General: MD5 fix, percent sign macro, CTAN upload	1
v2.0	\ST@sageplot : Change to use only keyword arguments: see issue 2 on bitbucket tracker	24
General: Add epstopdf option . .		21
Add final option		21
External Python scripts for parsing SageTeX-ified documents, tons of documentation improvements, sagetex.py refactored, include in Sage as spkg		1
Fixed up installation section, final <i>final</i> 2.0		3
Miscellaneous fixes, final 2.0 version		1
v2.0.1	General: Add T _E XShop info	4
v2.0.2	goboom : Make sure sys.exit sees a Python integer	41
v2.1	General: Add pausing support . . .	1
Get version written to .py file . .		1
v2.1.1	\ST@sage : Add ST@sage, sagestr, and refactor.	22
General: Add remote-sagetex.py script		1
Update parser module to handle pause/unpause		46
v2.2.1	RemoteSage : Fix stupid bug in do_inline() so that we actually write output to .sout file	54
v2.2.3	General: Rewrote installation section to reflect inclusion as standard spkg	3
v2.2.4	\ST@wsf : Add version mismatch checking.	20
sageexample : Add first support for sageexample environment . . .		28
v2.2.5	\ST@dodfsetup : Write sageexample environment contents to a separate file, formatted for doctesting	20
doctest : Fix up spacing in sageexample displaymath envs		38
v2.3	General: Add sagecommandline environment	1
v2.3.1	General: Handle filenames with spaces in SageTeXProcessor and sagecommandline env. . .	32
v2.3.2	\sageplot : Remove “.75 textwidth” default option . . .	24
General: Improve version mismatch check. Fixes trac ticket 8035. . .		32
v2.3.3	\ST@wsf : Improve version mismatch checking, include	

Mercurial revision in version	v3.0
string. 20	doctest: sageexample and sagecommandline now require “...” for continuation lines, not “...”; matches the actual Sage interpreter 38
inline: check label name when comparing against maximum counter seen; trac ticket 12267	34

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	\bfseries ... 24, 26, 27	sagecommandline 11, <u>232</u>
\% 129, 131	\blockbegin <u>382</u>	sageexample . 10, <u>200</u>
\' 1082	\blockend <u>382</u>	sagesilent .. 10, <u>192</u>
\(..... 925–927, 929	\boolean 140	sageverbatim 10, <u>196</u>
\) 925–927, 929		\equal 141, 144
\. 388	C	
\@bsphack . 180, 209, 243	\catcode 129, 131, 183, 211, 245	F
\@esphack . 195, 219, 253	\color 25–27, 33–35	\fbox 161
\@ifnextchar 135	\commandline <u>437</u>	\fi 125, 172, 178, 229, 263, 269, 273, 276
\@ifundefined 65, 77, 101, 105, 124, 146, 228, 262, 278	comment (environment) 10	\footnotesize 18
\@makeother 183, 210, 244	D	\framebox 133
\@ 424, 451, 769, 772, 819, 823	\d 925–927	G
\^ 183, 211, 245	\DeclareOption 92, 98, 103, 108	\gdef 89, 124, 157, 177, 228, 262
	\def 136, 188, 193, 197, 212, 246	\goboom <u>504</u>
\sq 501, 502, 505, 508, 524, 702	\definecolor 43–45	H
A	\DeSageTeX <u>748</u>	\hspace 189, 197
\abovedisplayshortskip 430	\do 183, 210, 244	I
\abovedisplayskip . 429	\doctest <u>411</u>	\IfFileExists 50, 94, 147, 163, 165
\active ... 183, 211, 245	\dospecials 183, 210, 244	\ifpdf 166
\AtBeginDocument .. . 65, 100, 104, 113	E	\ifST@paused ... 63, 120, 160, 224, 258, 266, 270, 274
\AtEndDocument 88, 94, 274	\else 122, 162, 168, 226, 260, 266	\ifthenelse 140, 141, 144
B	\end 123, 227, 261, 433, 463, 776, 777, 801	\immediate 67, 68, 79, 80, 88, 91
\begin 123, 227, 261, 417, 431, 461, 776, 777, 800	\endgroup 220, 254	\includegraphics 164, 790
\begingroup ... 208, 242	\endofdoc <u>515</u>	\initplot <u>357</u>
	\endverbatim .. 191, 199	\inline <u>363</u>
	environments:	
	comment 10	
	sageblock ... 10, <u>187</u>	

<code>\InputIfFileExists</code> . 111	<code>\PackageWarningNoLine</code> 94, 280	<code>\savecmd</code> 376
<code>\inputlineno</code> . . 116,	<code>\par</code> 189, 197	<code>\setboolean</code> 54
119, 137, 139,	<code>\parsedotsage</code> 923	<code>\setcounter</code> 58–60
181, 186, 204,	<code>\percent</code> 6, 129	<code>\setlength</code> 62, 234, 773
207, 223, 238,	<code>\plot</code> 469	<code>\SoutParser</code> 731
241, 257, 267, 271	<code>\ProcessOptions</code> . . . 110	<code>\space</code> 150, 155, 170, 175
J	<code>\progress</code> 351	<code>\splitsagecmds</code> 386
<code>\jobname</code> 67,	<code>\provideenvironment</code> 113	<code>\ST@beginsfbl</code>
71, 74, 79, 81,	R 179, 187, 192
83, 84, 94, 95,	<code>\ref</code> 123, 227, 261	<code>\ST@df</code> 78–80, 88, 91
111, 112, 132,	<code>\relax</code> 75, 90,	<code>\ST@diddfsetup</code> 89
267, 271, 275, 281	110, 266, 762, 763	<code>\ST@dodfsetup</code>
L	<code>\RemoteSage</code> 964 76, 206, 240
<code>\let</code> 183, 210, 244	<code>\renewcommand</code> 109	<code>\ST@endssfbl</code> 184, 191, 195
<code>\lstdefinlanguage</code> 5, 7	<code>\RequirePackage</code> 1–4,	<code>\ST@final</code> 93
<code>\lstdefinestyle</code> . . .	46–49, 51, 760, 761	<code>\ST@inclgrfx</code> . . 142,
. . 9, 21, 29, 37, 40	<code>\rule</code> 133, 161	143, 145, 158, 160
<code>\lstinputlisting</code> . . 446	S	<code>\ST@missingfilebox</code> .
M	<code>\S</code> 316	. 133, 148, 153, 173
<code>\mbox</code> 121, 225, 259	<code>\s</code> 387, 388, 556	<code>\ST@pausedfalse</code> 64, 272
N	<code>\sage</code> 6, 127, 724	<code>\ST@pausedtrue</code> 268
<code>\n</code> 318, 344, 375, 377,	<code>sageblock</code> (environ-	<code>\ST@plotdir</code> . . . 132,
387, 389, 390,	ment) . . . 10, 187	147, 150, 155,
399, 409, 424,	<code>\SageCodeExtractor</code> . 792	163–165, 170, 175
425, 436, 449,	<code>sagecommandline</code> (envi-	<code>\ST@rerun</code> 124,
468, 505, 508,	ronment) 11, 232	157, 177, 228, 262
525, 638, 648,	<code>\sagecommandlineskip</code>	<code>\ST@sage</code> . . 114, 127, 128
692, 819, 820, 233, 234, 444	<code>\ST@sageplot</code> . . 135, 136
823, 825, 826,	<code>\sagecommandlinetextoutput</code>	<code>\ST@sf</code> 66–68
831, 834, 838, 232, 256	<code>\ST@useimagemagick</code> . 99
900, 918, 970,	<code>sageexample</code> (environ-	<code>\ST@ver</code> 72, 74, 82
1027, 1060, 1111	ment) . . . 10, 200	<code>\ST@versioncheck</code> . .
<code>\newboolean</code> 53	<code>\sageexampleincludetextoutput</code> 74, 107, 109
<code>\newcounter</code> 55–57 200, 222	<code>\ST@wdf</code> 91, 207, 214,
<code>\newif</code> 63	<code>\sageplot</code> . . 7, 134, 725	230, 241, 248, 264
<code>\newlabel</code> 374, 734, 1060	<code>sagesilent</code> (environ-	<code>\ST@wsf</code> 68, 102, 106,
<code>\newlength</code> 61, 233	ment) . . . 10, 192	114, 136, 180,
<code>\newwrite</code> 66, 78	<code>\sagestr</code> 6, 128	185, 188, 193,
O	<code>\sagetexindent</code> . 10,	202, 213, 221,
<code>\openout</code> 67, 79	61, 62, 189, 197, 773	236, 247, 255,
<code>\or</code> 140	<code>\sagetexpause</code> 12, 266,	267, 271, 275, 277
P	266, 729, 762, 778	<code>\stepcounter</code>
<code>\PackageWarning</code> . . .	<code>\sagetexunpause</code> 126, 159, 231, 265
. 149, 154, 169, 174 12, 270,	T
	270, 730, 763, 778	<code>\TeX</code> . . 121, 161, 225, 259
	<code>sageverbatim</code> (environ-	<code>\textbf</code> 133
	ment) . . . 10, 196	<code>\textwidth</code> 787
		<code>\thepage</code>
		. 150, 155, 170, 175

<code>\theST@cmdline</code>	<code>\typeout</code> . . 112, 279, 283	213, 214, 247, 248
. . . . 239, 261, 262		<code>\verbatim@processline</code>
<code>\theST@inline</code>	U 188,
. . . . 117, 123,	<code>\usepackage</code> 557, 756, 759	193, 197, 212, 246
124, 205, 227, 228	<code>\UseVerbatim</code> 426	<code>\verbatim@start</code> . . .
<code>\theST@plot</code> . . . 138,	 194, 216, 250
147, 150, 155,	V	<code>\vspace</code> 444
163–165, 170, 175	<code>\verbatim</code> 190, 198	
<code>\toeps</code> <u>500</u>	<code>\verbatim@line</code> 188,	W
<code>\ttfamily</code> . 24–27, 32–35	189, 193, 197,	<code>\write</code> . . . 68, 80, 88, 91